

ÖLFLEX® 490 P/490 CP

Highly Abrasion-Resistant Control Cable with PUR Jacket & UL/CSA AWM; Unshielded & Shielded



ÖLFLEX® 490 P is a flexible control cable with a rugged, highly abrasion-resistant polyurethane jacket. It is UV-resistant and performs very well in mineral oils, cutting oils, and areas with high mechanical abuse. ÖLFLEX® 490 CP is the shielded version, with an overall foil tape with drain wire and tinned copper braid for EMI and RFI protection.

Recommended Applications

Machine tool equipment; handheld controls; submersible applications; any areas where the cable can be cut and damaged by sharp objects

Approvals



Unshielded Construction

Conductors: Finely stranded bare copper

Insulation: Specially blended PVC

Jacket: Specially formulated gray polyurethane

Shielded Construction

Conductors: Finely stranded bare copper

Insulation: Specially blended PVC

Shielding: Overall foil tape wrap with drain wire; tinned copper braid (85% coverage)

Jacket: Specially formulated gray polyurethane

Application Advantage

- Rugged PUR jacket to resist cuts, nicks, and abrasion
- UL & CSA AWM approved
- Extremely oil and chemical resistant
- Able to be dragged on the floor with minimal damage
- Number-coded for easy wiring

Cable Attributes, see page 659

OR-05	FR-02	FL-01	MP-06
OIL	FLAME	MOTION	MECHANICAL

Similar Cables

- ÖLFLEX® 590 P/590 CP
- ÖLFLEX® 190/190 CY

Complete the Installation

	SKINTOP® Strain Relief: page 502		EPIC® Connectors: page 278
--	--	--	----------------------------------

Technical Data	
Minimum Bend Radius:	<ul style="list-style-type: none"> - for installation: 4 x cable diameter - shielded: 6 x cable diameter
Temperature Range:	<ul style="list-style-type: none"> - for flexible use: -10°C to +80°C - for stationary use: -20°C to +80°C
Nominal Voltage:	600V
Test Voltage:	2000V
Conductor Stranding:	Class 5 fine wire*
Color Code:	Black with white numbers, plus green/yellow ground
Approvals:	UL: AWM 20234 Attributes: UL Oil Res I/II Sunlight Resistant NFPA 79 2012 Canada: CSA AWM I/II A/B FT1 Additional: CE & RoHS

* 18 AWG meets only the Class 5 cross section and DC resistance

Photographs are not to scale and are not true representations of the products in question. For current information go to our website. If not otherwise specified, all values relating to the product are nominal values.

ÖLFLEX® 490 P

Part Number	Number of Conductors (incl. ground)	Nominal Outer Diameter (inches) (mm)		Copper Weight (lbs/mft)	Approx. Weight (lbs/mft)	SKINTOP® Non-Metallic PG Thread	Part Number	Number of Conductors (incl. ground)	Nominal Outer Diameter (inches) (mm)		Copper Weight (lbs/mft)	Approx. Weight (lbs/mft)	SKINTOP® Non-Metallic PG Thread
20 AWG (0.50 mm²)							16 AWG (1.50 mm²)						
402002*	2	0.245	6.2	7	35	S1107	401602*	2	0.295	7.5	20	53	S1111
402003	3	0.256	6.5	10	40	S1109	401603	3	0.310	7.9	29	64	S1111
402004	4	0.274	7.0	13	46	S1109	401604	4	0.333	8.5	39	77	S1111
402005	5	0.293	7.4	17	53	S1111	401605	5	0.360	9.1	48	90	S1111
402007	7	0.313	8.0	23	66	S1111	401607	7	0.388	9.9	68	115	S1113
402009	9	0.355	9.0	30	82	S1111	401609	9	0.446	11.3	88	141	S1113
402012	12	0.401	10.2	38	106	S1113	401612	12	0.496	12.6	117	179	S1116
402018	18	0.459	11.7	59	139	S1113	401618	18	0.574	14.6	175	253	S1121
402025	25	0.534	13.6	79	176	S1121	401625	25	0.654	16.6	242	335	S1121
18 AWG (1.00 mm²)							14 AWG (2.50 mm²)						
401802*	2	0.269	6.8	13	44	S1109	401402*	2	0.329	8.4	33	66	S1111
401803	3	0.281	7.1	20	51	S1111	401403	3	0.347	8.8	49	75	S1111
401804	4	0.303	7.7	26	64	S1111	401404	4	0.374	9.5	65	108	S1111
401805	5	0.325	8.3	31	75	S1111	401405	5	0.406	10.3	81	121	S1113
401807	7	0.349	8.9	46	93	S1111	401407	7	0.439	11.2	113	170	S1113
401809	9	0.399	10.1	59	119	S1113	401409	9	0.507	12.9	146	194	S1116
401812	12	0.451	11.5	79	143	S1113	401412	12	0.567	14.4	194	238	S1121
401818	18	0.519	13.2	118	203	S1116	401418	18	0.659	16.7	290	357	S1121
401825	25	0.607	15.4	164	264	S1121	401425	25	0.754	19.2	404	474	S1129

* 2c cable does not include ground.

ÖLFLEX® 490 CP

Part Number	Number of Conductors (incl. ground)	Nominal Outer Diameter (inches) (mm)		Copper Weight (lbs/mft)	Approx. Weight (lbs/mft)	SKINTOP® MS-SC PG Thread	Part Number	Number of Conductors (incl. ground)	Nominal Outer Diameter (inches) (mm)		Copper Weight (lbs/mft)	Approx. Weight (lbs/mft)	SKINTOP® MS-SC PG Thread
20 AWG (0.50 mm²)							16 AWG (1.50 mm²)						
402002CP*	2	0.270	6.9	19	46	53112210	401602CP*	2	0.320	8.1	43	73	53112220
402003CP	3	0.281	7.1	24	55	53112220	401603CP	3	0.335	8.5	50	82	53112220
402004CP	4	0.299	7.6	27	66	53112220	401604CP	4	0.358	9.1	60	97	53112220
402005CP	5	0.318	8.1	33	73	53112220	401605CP	5	0.385	9.8	76	112	53112230
402007CP	7	0.338	8.6	40	84	53112220	401607CP	7	0.413	10.5	98	137	53112230
402009CP	9	0.380	9.7	53	104	53112230	401609CP	9	0.477	12.1	122	170	53112240
402012CP	12	0.426	10.8	69	117	53112230	401612CP	12	0.527	13.4	156	216	53112240
402018CP	18	0.490	12.4	90	163	53112240	401618CP	18	0.605	15.4	231	295	53112250
402025CP	25	0.565	14.4	119	214	53112250	401625CP	25	0.685	17.4	307	384	53112260
18 AWG (1.00 mm²)							14 AWG (2.50 mm²)						
401802CP*	2	0.294	7.5	28	62	53112220	401402CP*	2	0.354	9.0	56	84	53112220
401803CP	3	0.306	7.8	35	71	53112220	401403CP	3	0.372	9.4	76	101	53112230
401804CP	4	0.328	8.3	44	82	53112220	401404CP	4	0.399	10.1	96	123	53112230
401805CP	5	0.350	8.9	51	95	53112220	401405CP	5	0.431	10.9	116	145	53112230
401807CP	7	0.374	9.5	70	117	53112230	401407CP	7	0.470	11.9	149	183	53112240
401809CP	9	0.424	10.8	89	139	53112230	401409CP	9	0.538	13.7	188	225	53112250
401812CP	12	0.473	12.0	110	176	53112240	401412CP	12	0.598	15.2	242	287	53112250
401818CP	18	0.540	13.7	155	240	53112250	401418CP	18	0.690	17.5	359	390	53112260
401825CP	25	0.609	15.5	218	311	53112250	401425CP	25	0.785	19.9	479	558	53112260

* 2c cable does not include ground.

Recommended SKINTOP® assumes minimal OD variance. Additional configurations are available, please see our SKINTOP® Section. Photographs are not to scale and are not true representations of the products in question. For current information go to our website. If not otherwise specified, all values relating to the product are nominal values.