

## SILVYN® HYGIENIC

The stainless steel fitting SILVYN® HYGIENIC is designed in accordance with the industrial hygiene requirements

### Info

Ideal for hygienic critical areas - resistant, edge-free, robust and reliable

No gaps, voids or outer lying thread - so no risk of contamination of food machines, facilities or components.



# CE



Waterproof



Temperature-resistant



Reliability



Robust



Oil-resistant



Mechanical resistance



Corrosion-resistant



Good chemical resistance



Mechanical and plant engineering



Food & Beverage

Last Update (18.03.2019)

©2019 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## SILVYN® HYGIENIC



Cold-resistant

### Benefits

Hygienic Design for ideal cleaning results

Smooth surfaces and no edges prevent the accumulation of fluids and formation of micro-organisms

### Application range

Food machinery, equipment and components

Pharmaceutical industry

Mechanical engineering

### Product features

High chemical and thermal stability with very aggressive media such as Detergents and disinfectants, acids and alkalis during cleaning processes etc.

### Norm references / Approvals

DIN EN 1672-2

Guideline for the design of machinery

DIN EN ISO 14 159

Security of machinery – Hygienic requirements for the design of machinery

### Product Make-up

Material and shape provide an easy and safe cleaning

By the blue coloring of the sealing material clearly distinguishable from foodstuffs

Rounded key areas for mounting with standard tools

### Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC001180 ETIM 5.0 Class-Description: Screw connection for protective metallic hose
Classification ETIM 6:	ETIM 6.0 Class-ID: EC001180 ETIM 6.0 Class-Description: Screw connection for protective metallic hose
Norm references / Approvals:	IEC EN 61386-23
Material:	Body: Stainless Steel (Grade 316) Insert: Nickel Plated Brass Inner seal: Polyamide 6 Sealing material: Special Elastomer
Protection rating:	IP66 IP67 IP68 (2 bar) IP69
Temperature range:	-50°C to +135°C

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

Last Update (18.03.2019)

©2019 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

**SILVYN® HYGIENIC**

Article number	Metric size	Clear opening (mm)	Suitable conduit nominal size
SILVYN® HYGIENIC			
55510700	16 x 1.5	10.7	3/8"
55510701	20 x 1.5	14.5	1/2"
55510702	25 x 1.5	18.7	3/4"
55510703	32 x 1.5	24.6	1"
55510704	40 x 1.5	32.7	1 1/4"
55510705	50 x 1.5	37.7	1 1/2"
55510706	63 x 1.5	49	2"

Last Update (18.03.2019)

©2019 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)You can find the current technical data in the corresponding data sheet.  
PN 0456 / 02\_03.16