



Installation simplified

Philips ballast bypass (UL Type B) T8 LED lamps use a double-ended design which significantly simplifies installation, saving time and costs. This product can replace either T8 or T12 lamps in fixtures containing shunted or non-shunted G13 (medium bi-pin) lamp holders.

- Proven energy savings - over 40% energy savings¹ over fluorescent systems
- Lifetime delivered – average life rating of 50,000 hours² means satisfied customers
- UL Classified and double-ended design for safety
- Ballast Bypass - UL Type-B
- Installation simplicity - can be used with both shunted and non-shunted sockets
- Light quality and performance predictability - consistent light output and no flicker means satisfied happy customers and no wasted time redoing a job.
- Proven product history and a company with a long history of innovation and reliability in the lighting industry.
- Wide beam light distribution - 240°



Philips MainsFit LED lamps

Ordering, Electrical and Technical Data (Subject to change without notice)

Product Number	Model Number	DLC Product ID	Order Code	Volts (Depending on Ballast)	Base	CRI	Color Temp. (K)	Pkg Qty	Lamp Lifetime ³	MOL (in.)	Beam Angle
MainsFit LED T8 - 4ft											
47731-5	9290018454	P3V56EPW	14T8PRO/48-830/BB17/G 10/1 FB	120-277	G13	82	3000	10	50,000	48	240°
47732-3	9290018455	PN3X1615	14T8PRO/48-835/BB17/G 10/1 FB	120-277	G13	82	3500	10	50,000	48	240°
47733-1	9290018456	PTLPG7HI	14T8PRO/48-840/BB18/G 10/1 FB	120-277	G13	82	4000	10	50,000	48	240°
47734-9	9290018457	PDSO3H88	14T8PRO/48-850/BB18/G 10/1 FB	120-277	G13	82	5000	10	50,000	48	240°
MainsFit LED T8 High Output - 4ft											
47174-8	9290013631	PHYVFGFP	16.5T8PRO/48-830/BB20/G	120-277	G13	82	3000	10	50,000	48	240°
47175-5	9290013632	PV2NCR1M	16.5T8PRO/48-835/BB20/G	120-277	G13	82	3500	10	50,000	48	240°
47176-3	9290013633	PUQ8ZEAH	16.5T8PRO/48-840/BB21/G	120-277	G13	82	4000	10	50,000	48	240°
47177-1	9290013634	P8HU6SVS	16.5T8PRO/48-850/BB21/G	120-277	G13	82	5000	10	50,000	48	240°

Technical data (Subject to change without notice)

Product No.	Bare Lamp Watts (W)	Initial Lumens	Beam Angle	Dimmable
MainsFit LED T8 - 4ft				
47731-5	14	1700	240°	N
47732-3	14	1700	240°	N
47733-1	14	1800	240°	N
47734-9	14	1800	240°	N
MainsFit LED T8 High Output - 4ft				
47174-8	17	2000	240°	N
47175-5	17	2000	240°	N
47176-3	17	2100	240°	N
47177-1	17	2100	240°	N

For more information on Philips' limited warranty please visit www.philips.com/warranties.

Philips MainsFit LED lamps

Shipping data (Subject to change without notice)

Product Number	SKU UPC (0-46677)	Outer Bar Code (5-00-46677)	Case Qty.	Case Weight (lbs)	Case Volume (cu. ft.)	Pallet Qty	Lamps / SKU	SKU's per layer	Layers High	SKU Dimensions (L x W x H) (in.)	Case Dimensions (L x W x H) (in.)	Pallet Dimensions (L x W x H) (in.)
MainsFit LED T8 - 4ft												
47731-5	47731-8	47731-3	10	6.65	0.42	550	1	50	11	1.1 x 1.1 x 47.6	49.5 x 7.1 x 3.9	50.0 x 35.9 x 42.6
47732-3	47732-5	47732-0	10	6.65	0.42	550	1	50	11	1.1 x 1.1 x 47.6	49.5 x 7.1 x 3.9	50.0 x 35.9 x 42.6
47733-1	47733-2	47733-7	10	6.65	0.42	550	1	50	11	1.1 x 1.1 x 47.6	49.5 x 7.1 x 3.9	50.0 x 35.9 x 42.6
47734-9	47734-9	47734-4	10	6.65	0.42	550	1	50	11	1.1 x 1.1 x 47.6	49.5 x 7.1 x 3.9	50.0 x 35.9 x 42.6
MainsFit LED T8 High Output - 4ft												
47174-8	47174-3	47174-8	10	6.20	0.42	550	1	50	11	1.1 x 1.1 x 47.6	50 x 35.9 x 3.9	50.0 x 35.9 x 42.6
47175-5	47175-0	47175-5	10	6.20	0.42	550	1	50	11	1.1 x 1.1 x 47.6	50 x 35.9 x 3.9	50.0 x 35.9 x 42.6
47176-3	47176-7	47176-6	10	6.20	0.42	550	1	50	11	1.1 x 1.1 x 47.6	50 x 35.9 x 3.9	50.0 x 35.9 x 42.6
47177-1	47177-4	47177-9	10	6.20	0.42	550	1	50	11	1.1 x 1.1 x 47.6	50 x 35.9 x 3.9	50.0 x 35.9 x 42.6

1. Savings based on comparison to F32T8 electronic instant start systems.
2. Tested to B50 L70 requirement
3. Lamp lifetime means the length of time (in hours) until half of the LED light sources maintain at least 70% of their initial lumen output (B50, L70).
4. Photometric testing consistent with IES LM-79.
5. Product is not dimmable
6. Modifications to the product void the warranty

© 2017 Philips Lighting Holding B.V. All rights reserved. Philips reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.



Philips Lighting North America Corporation
200 Franklin Square Drive, Somerset, NJ 08873
Tel. 855-486-2216

Philips Lighting Canada Ltd.
281 Hillmount Rd, Markham, ON, Canada L6C 2S3
Tel. 800-668-9008