

### CENTRAL VACUUM KIT MODEL VXKIT300A



#### VX3000C POWER UNIT SPECIFICATIONS

Motor	2-Stage Universal bypass
Horsepower Rating	2.2 @ Full open intake
Amperes	12
Voltage	120 VAC
Airflow at 2" (50.8 mm) opening	.114 CFM (53.8 L/s)
Water Lift	.90" (2.3 m)
Air Watts	.475
Switch on Power Unit	Yes
Utility Valve with Power Unit	Yes
Recommended Circuit	15 Amp
Primary Filtration	Self-cleaning, high efficiency permanent cloth filter
Capacity	4 U.S. Gallons (15.1 Litres)
Secondary Filtration	Yes
cULus Listed	Yes
Housing	Corrosion resistant engineered thermoplastic
Power Unit Dimensions	11.5" D x 16.5" W x 36" H

Designed for smaller homes up to 3,000 square feet (279 m<sup>2</sup>) or budget minded consumers. This power unit features a specially designed 2-stage motor that delivers 475 air watts of power. It's the most powerful power unit in its class. The unique oval shape offers space saving advantages and efficient cyclonic filtration.

#### FEATURES

- Internal sound suppression system makes it the quietest power unit in its class
- Easy access door for cyclonic filter maintenance
- Oversized debris pail handles made for quick and easy pail removal
- Dual vacuum air intakes allow for connecting to the tubing line from the right side, left side or both

- Large 4 U.S. gallons (15.1 litres) easy-clean, corrosion resistant debris pail that typically needs emptying only every 6 months
- Six foot (1.8 m) long power cord
- Multi-surface brush for carpet, tile, wood and ceramic
- Standard accessory kit including:  
32' low-voltage crushproof hose, deluxe hose hanger, 10" wide hard floor brush, stainless steel ratchet telescopic wand, natural bristle upholstery tool, square faced dusting brush, 9" crevice tool with notched end, clip-on caddy
- cULus Listed
- Limited Lifetime Warranty



Broan-NuTone Canada Inc.; Mississauga, Ontario [www.broan.ca](http://www.broan.ca) 1-888-882-7626

PROJECT	REMARKS
LOCATION	
MODEL No.	
QTY.	
SUBMITTED BY	
DATE	