

4587 - 4591

- Taper Pin Reamer (Taper: 1/4" per foot)
- Alésoir machine cône morse conique
- Escariadores para pasadores cónicos



4587



- 1.1 1.2 1.3 1.4 2.1 3.1 4.1 6.2
- 1.5 1.6 2.2 2.3 3.2 3.3 3.4 4.2 4.3 5.1 5.2 5.3 6.1 6.3 6.4 7.1 7.2 7.3 7.4 8.2

nom Ø	d ₁ Ø _{small} Inch	d ₁ Ø _{large} Inch	d ₂ Ø Inch	l ₂ Inch	l ₁ Inch	# Flutes	EDP #
0	0.1287	0.1638	11/64	1.11/16	2.15/16	6	5011129
1	0.1447	0.1798	3/16	1.11/16	2.15/16	6	5011130
2	0.1600	0.201	13/64	1.15/16	3.3/16	6	5011131
3	0.1813	0.2294	15/64	2.5/16	3.11/16	6	5011132
4	0.2071	0.2600	17/64	2.9/16	4.1/16	6	5011133
5	0.2410	0.2994	5/16	2.13/16	4.5/16	6	5011134
6	0.2773	0.354	23/64	3.11/16	5.7/16	6	5011135
7	0.3297	0.422	13/32	4.7/16	6.5/16	6	5011136
8	0.3971	0.505	7/16	5.3/16	7.3/16	6	5011137
9	0.4800	0.6066	9/16	6.1/16	8.5/16	8	5011138
10	0.5799	0.7216	5/8	6.13/16	9.5/16	8	5011139

4591

- Taper Pin Reamer, Left Hand Spiral Flute
- Alésoir machine cône morse conique
- Escariadores para pasadores cónicos
- (Taper: 1/4" per foot)



- 1.1 1.2 1.3 1.4 2.1 3.1 4.1 6.2
- 1.5 1.6 3.2 3.3 3.4 4.2 4.3 5.1 5.2 5.3 6.1 6.3 6.4 7.1 7.2 8.2

nom Ø	d ₁ Ø _{small} Inch	d ₁ Ø _{large} Inch	d ₂ Ø Inch	l ₂ Inch	l ₁ Inch	# Flutes	EDP #
0	0.1287	0.1638	11/64	1.11/16	2.15/16	6	5011146
1	0.1447	0.1798	3/16	1.11/16	2.15/16	6	5011147
2	0.1600	0.201	13/64	1.15/16	3.3/16	6	5011148
3	0.1813	0.2294	15/64	2.5/16	3.11/16	6	5011149
4	0.2071	0.2600	17/64	2.9/16	4.1/16	6	5011150
5	0.2410	0.2994	5/16	2.13/16	4.5/16	6	5011151
6	0.2773	0.354	23/64	3.11/16	5.7/16	6	5011152
7	0.3297	0.422	13/32	4.7/16	6.5/16	6	5011153
8	0.3971	0.505	7/16	5.3/16	7.3/16	6	5011154
9	0.4800	0.6066	9/16	6.1/16	8.5/16	8	5011155
10	0.5799	0.7216	5/8	6.13/16	9.5/16	8	5011156

■ = EXCELLENT FOR APPLICATION
• = GOOD FOR APPLICATION