**3F** 

## WLRS, WLRD and WLGF Wet Location Covers


Covers with and without NEMA Configuration Receptacles									
Туре	Volts	NEMA Configuration	Complete Cover with Receptacle Assy. Cat. #	Spring Door Cover & Gasket Only Cat. #‡	Туре	Volts	NEMA Configuration	Complete Cover with Receptacle Assy. Cat. #	Spring Door Cover & Gasket Only Cat. #‡
Single Device					Duplex D	evice			
		_	F	ng Blade P	lugs	_			
2-Pole 3-Wire Grounding 15 Amp	125V	5-15R	WLRS-5-15	WLRS-1	2-Pole 3-Wire Grounding 15 Amp	125V	5-15R	WLRD-5-15	WLRD-1
	250V	(O) 6-15R	WLRS-6-15	WLRS-1		250V	0 6-15R	WLRD-6-15	WLRD-1
2-Pole 3-Wire Grounding 20 Amp	125V	0 1 b 5-20R	WLRS-5-20	WLRS-1	2-Pole 3-Wire Grounding 20 Amp	125V	0 1 B 5-20R	WLRD-5-20	WLRD-1
	250V	0 6-20R	WLRS-6-20	WLRS-1		250V	© 6-20R	WLRD-6-20	WLRD-1
For Locking Blade Plugs									
2-Pole 3-Wire Grounding 15 Amp	125V	L5-15R	WLRS-L5-15	WLRS-1	2-Pole 3-Wire Grounding 15 Amp	125V	(5) L5-15R	WLRD-L5-15	WLRD-1
	250V	€ L6-15R	WLRS-L6-15	WLRS-1					
2-Pole 3-Wire Grounding 20 Amp	125V	(P) L5-20R	WLRS-L5-20	WLRS-2					
	250V	(P) L6-20R	WLRS-L6-20	WLRS-2					

## **Wet Location Covers for GFCI Duplex Receptacles**



Cat. No. Description


WLGF For Flush Device Boxes Spring Door Cover & Gasket Only Cat # WLFG





Cat. No. Description

WLGF-FS For FS and FD Cast Device Boxes Spring Door Cover & Gaset Only Cat. # WLGF-FS



<sup>‡</sup> Must be used with a wet locations rated wiring device.