ED PAR30



3.63 IN					
Electrical					
Watt	13				
Power Factor	> 0.9				
Voltage	120 volt				
Frequency	60Hz				
Base Type	E26 Medium				
Operating Temperature Range	-4F to 104F				
Light					
Initial Lumens	800				
Lumens per Watt	62				
Color Temperature	4000K				
Color Rendering (CRI)	93				
Beam Angle	40°				
Agency Approvals					
UL	Yes				
Energy Star	25,000 hours				
RoHS	Yes				
FCC	Yes				
Product Details					
Warranty	10 years 6 hr/day				
Diameter	3.63"				
Nominal Length	4.59"				

800 Lumen 13 Watt 4000K PAR30 - 40° Commercial Pack




PRODUCT DESCRIPTION

13 watt PAR30 EarthBulb LED floodlight replaces 75 watt incandescent floodlights for over 85% energy savings. Great for use in dimming recessed lighting, track lighting and display lighting applications. High power LED and an advanced cooling system provides for 25,000 hours of LED life. Medium screw base. Suitable for outdoor use, damp location rated.

PRODUCT FEATURES

- Dimming PAR30 flood light provides 800 lumens, capable of dimming to less ٠ than 5%
- 40° beam angle provides a flood, not spot light
- Unique LED array design look like halogen when powered on
- Chipset provides 4000K cool white light with a high color rendering rating over 80, 90+ CRI
- Wet rated UL and suitable for exterior locations
- Face of the lamp looks like standard PAR lamps
- Fits track heads like a PAR lamp is intended



Intensity (Candlepower) Summary at 25°C - Candelas

45

1947

1875

1655

1279

840.9

477.4

250.3

133.2

77.8

52.2

38.8

30.2

23.9

18.6

14.1

10.1

6.7

4.3

2.3

67.5

1947

1863

1632

1251

820.3

466.8

248.9

135.4

79.8

52.9

38.7

30.0

23.5

18.2

13.6

9.7

6.5

4.1

22

90

1947

1852

1604 1209

779.2

440.8

241.3

131.2

78.2

52.1

38.0

29.4

23.2

17.8

13.2

9.4

6.2

3.8

2.0

22.5

1947

1887

1683

1310

858.4

484.1

249.6

131.7

76.9

51.6

38.5

30.1

23.9

18.7

14.1

10.2

6.9

4.4

2.5

0

1947

1904

1712

1354

903.8

515.6

265.4

137.8

79.9

53.0

39.2

30.7

24.4

19.2

14.5

10.6

7.2

2.7

H(°)

0 5

10

15

20

25

30

35

40

45

50

55

60

65

70

75

80

85 4.7


90

PRODUCT APPLICATIONS





LUMINOUS DISTRIBUTION INTENSITY DIAGRAM LUMINOUS DISTRIBUTION INTENSITY DATA



MODEL NUMBER: LP31340D6 ORDER CODE: 10436

				_
Order Code	Individual UPC	Master Park UPC	Qty	Master Pack
10436	840791104361	84079110436100	12	
Dimensions (inches - Length x Width x Height)				
10436	3.93 x 3.93 x 5.08	16.61 x 12.55 x 6.14	12	
Weight (lbs)				
10436	.449	6.622	12	





Individual