# LED A19



Electrical						
Watt	9.5					
Power Factor	> 0.9					
Voltage	120 volt					
Frequency	60Hz					
Base Type	E26 Medium					
Operating Temperature Range	-4F to 104F					
Light						
Initial Lumens	810					
Lumens per Watt	85					
Color Temperature	2700K					
Color Rendering (CRI)	80+					
Agency Approvals						
UL	Yes					
Energy Star V2.1	15,000 hours, Rated for enclosed fixtures					
RoHS	Yes					
FCC	Yes					
Product Details						
Warranty	5 years 6 hr/day					
Diameter	2.42"					
Nominal Length	4.63"					
Rated Life	15,000 hours					

## 810 Lumen 9.5 Watt 2700K A19 Omni LED



#### PRODUCT DESCRIPTION


9.5 watt A19 Omni-directional EarthBulb LED provides 810 lumens and replaces 60 watt incandescent directional bulbs for over 80% energy savings. 2700K color of light is standard. Great for use in table lamps, floor lamps, wall sconce, and task lighting applications. Multi-Chipset LED and an advanced cooling system provides for 15,000 hours of LED life. Medium screw base. Energy Star rated product (ES V2.1). Suitable for outdoor use, damp location, when installed in fixtures and not directly exposed to weather. Energy Star rated to be used in enclosed fixtures.

### **PRODUCT FEATURES**

- This A bulb is Energy Star (V2.1) and provides 810 lumens, capable of dimming to less than 5%
- Omni directional beam angle provides full radial illumination
- Chipset provides 2700K soft white with a high color rendering rating of over 81
- New heat sync system provides improved aesthetics and performance
- May be used in enclosed fixtures



#### **LUMINOUS DISTRIBUTION INTENSITY DIAGRAM**



AVERAGE BEAM ANGLE (50%):225.3°
Note: IES files available upon request.

MODEL NUMBER: LA19927DEFV2

Individual	Inner Pack	Master Pack

Order Code	Pack Size	Individual UPC	Inner Pack UPC	Qty	Master Park UPC	Qty	
10761	1	840791107614	00840791107614	12	84079110761400	48	
Dimensions (inches - Length x Width x Height)							
10761	1	2.44 x 2.44 x 4.72	10.47 x 7.91 x 5.39	12	21.73 x 16.61 x 6.73	48	
Weight (lbs)							
10761	1	0.20	2.35	12	9.40	48	





