LED Wall Pack

LED Wall Pack 30W - Adjustable 3000 Lumens 4000K





Electrical	
Watt	30
Voltage	100-277V
Power Factor	>0.9
Min. Start Temperature	-31°F
Max. Operating Temperature	122°F
Light	
Initial Lumens	3000
Lumens per Watt	100
Color Temperature	4000K
Color Rendering (CRI)	>80
Beam Angle	V:105±10° H:85±10°
Agency Approvals	
DLC	Yes
CSA	No
FCC	Yes
ETL	Yes
Product Details	
Housing Material	Aluminum
Lens Material	Glass
Warranty	5 year 10 year limited
Rated Life	50,000 hours

PRODUCT DESCRIPTION

The EarthTronics adjustable wall pack can be locked in to any angle ranging from 0° to 90° providing exterior security illumination where required. The durable die cast aluminum housing is powder coated to maintain the fixture appearance for several years. This 30 watt wall pack operates at 100 lumens per watt efficiency and provides 3000 lumens. 4000K color of light and the high 80+ CRI provide bright illumination. Accepts 100 – 277 volt AC power supply. The long 50,000 hour is backed up with a 10 year limited warranty. The wall pack fixture requires a properly anchored UL recognized junction box for proper installation.

PRODUCT FEATURES

- High Quality Die Cast Aluminum Housing
- Durable bronze powder coat finish
- 0 90° adjustable beam angle locks in position
- · Suited for wall mounting to provide a wide flood area
- · IP65 rated for wet location use
- Contemporary design compliments building exteriors
- · DLC listed
- 120-277 volt constant current driver
- 50,000 hour rated life L70

Order Code: WP04A270040BK1

Model #: WP04A270040

DLC Product ID: PP69MSGM

DIMENSIONS:

Diameter: 6.22 inches

· Nominal Length: 7.40 inches

WEIGHT: 3.30 lbs

CAUTION: If the fixture is to be removed or replaced, please ensure that they electricity is switched off and that the fitting is cool before touching it





