# **SIEMENS**

# Data sheet

# 6GK5008-0BA10-1AB2

SCALANCE XB008 Unmanaged Industrial Ethernet Switch for 10/100 Mbit/s for setting up small star and line topologies; LED diagnostics, IP20, 24 V AC/DC power supply, with 8x 10/100 Mbit/s twisted pair ports with RJ45 sockets; Manual available as a download



Product type designation	SCALANCE XB008	
Transmission rate		
Transfer rate	10 Mbit/s, 100 Mbit/s	
Interfaces / for communication / integrated		
Number of electrical connections		
• for network components or terminal equipment	8; RJ45	
Number of 100 Mbit/s SC ports		
• for multimode	0	
Interfaces / others		
Number of electrical connections		
• for power supply	1	
Type of electrical connection		
• for power supply	3-pole terminal block	
Supply voltage, current consumption, power loss		
Type of voltage / of the supply voltage	AC/DC	
Supply voltage		
• external	24 V	

• automal / minimum	19.2 V
external / minimum	
external / maximum	28.8 V
• at AC	24 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	0.6 A / 60 V
Consumed current / maximum	0.12 A
Power loss [W]	
• at DC / at 24 V	2.88 W
Permitted ambient conditions	
Ambient temperature	
<ul><li>during operation</li></ul>	-10 +60 °C
<ul><li>during storage</li></ul>	-40 +80 °C
during transport	-40 +80 °C
Relative humidity	
<ul> <li>at 25 °C / without condensation / during</li> </ul>	95 %
operation / maximum	
Protection class IP	IP20
Design, dimensions and weight	
Design	Box
Width	45 mm
Height	100 mm
Depth	87 mm
Net weight	0.18 kg
Mounting type	
<ul> <li>35 mm DIN rail mounting</li> </ul>	Yes
<ul><li>wall mounting</li></ul>	Yes
• S7-1500 rail mounting	No
Product functions / management, configuration	
Product function	
<ul> <li>multiport mirroring</li> </ul>	No
• CoS	Yes
PROFINET conformity class	A
Product function / switch-managed	No
Product functions / Redundancy	
Product function	
<ul> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	Yes
Parallel Redundancy Protocol  (DDD)/Dadwadayt Naturals Assass (DNA)	No
(PRP)/Redundant Network Access (RNA)	
Standards, specifications, approvals	

Standard

FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, for FM

GP. IIC, T4

EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc. • for hazardous zone

KEMA 07ATEX0145 X

UL 60950-1, CSA C22.2 No. 60950-1 • for safety / from CSA and UL

EN 61000-6-4 (Class A) • for emitted interference

EN 61000-6-2 • for interference immunity

# Standards, specifications, approvals / CE

Certificate of suitability / CE marking Yes

Yes

### Standards, specifications, approvals / miscellaneous

Certificate of suitability EN 61000-6-2, EN 61000-6-4

• C-Tick

 KC approval Yes

#### Standards, specifications, approvals / product conformity

**MTBF** 214 y

#### Accessories

# Further Information / Internet Links

#### Internet-Link

• to website: Selector SIMATIC NET

**SELECTION TOOL** 

• to website: Industrial communication

• to website: Industry Mall

• to website: Information and Download Center

• to website: Image database

• to website: CAx Download Manager

• to website: Industry Online Support

http://www.siemens.com/snst

http://www.siemens.com/simatic-net

https://mall.industry.siemens.com

http://www.siemens.com/industry/infocenter

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

https://support.industry.siemens.com

#### Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Thirdparty products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about

product updates as they occur, sign up for a product-specific newsletter. For more information, visit

http://support.automation.siemens.com. (V3.4)