

Three Pole Definite Purpose Contactors with AC Coil (Open Type only)

Full Load Amps	Locked Rotor Amps			Resistive Amps Ⓣ	Maximum Horsepower Ⓢ						Catalog Number	Price Each	Std. Pkg.	
					10			30						
	240V Ⓢ	480V	600V		120V	200	240V	200V	240V	480V				600V
30 ❶	180	150	120	40	2	~	5	10	10	15	20	CDP2-B3P30A-* ❷	109.45	25
40	240	200	160	50	3	~	7-1/2	10	10	20	25	CDP2-B3P40A-* ❸	133.07	25
50	300	250	200	65	3	7-1/2	10	15	15	25	25	CDP2-C3P50A-*	255.40	15
60	360	300	240	75	5	7-1/2	10	25	25	30	30	CDP2-C3P60A-*	296.17	15
75	450	375	300	93	5	10	15	20	25	40	40	CDP2-D3P75A-*	386.32	1
90	540	450	360	120	7-1/2	15	20	25	30	50	50	CDP2-D3P90A-*	534.41	1



Series CDP2 3-pole contactor

Auxiliary Contacts for 3 Pole Contactors

Auxiliary	Description	Circuit Diagram	Catalog Number	Price
	Two pole Auxiliary Contact Block (1-NO / 1-NC) - Side mount with quick connect stabs for 25...40A, 3 pole contactors for 50...90A, 3 pole contactors		CDP2-BE-11 ❹	41.85
			CDP2-CD-11 ❺	43.26
	One pole Auxiliary Contact Block (SPDT) - Side mount with quick connect stabs for 25...40A, 3 or 4 pole contactors		CDP2-BE-1SPDT ❻	36.93

AC Coil Codes

AC Coil Code	Voltage Range
	60 Hz
24	24V
120	120V
220W	208-240V
277	277V
480	480V

Ordering Instructions

Specify Catalog Number	
Replace (*) with Coil Code	See Coil Codes on this page

- ❶ 25A contactors available by special order. Contact your Sprecher + Schuh representative.
- ❷ 240V rating also applies to 277V applications.
- ❸ Box lugs are supplied as standard. Screw terminals are available on the power connections by special order only in quantity.
- ❹ Screw power terminals are supplied standard on 25 and 30A contactors. Box Lugs available by special order only in quantity.
- ❺ Meets NEMA Standard B600. See page A7 for technical details.
- ❻ Meets NEMA Standard B600 EXCEPT has 10 A continuous current rating.