#S13SXGBFN

SuperiorTouch®

Cut-Resistant Foam Nitrile Palm-Coated Gloves with Dyneema®

#S13SXGBFN

Dyneema®
The softer strength

Dyneema® is 15 times stronger than steel on an equal weight basis and twice as strong as Kevlar®. It is also a lint-free, continuous filament yarn. With their high coefficient of friction, nitrile palm coating and glove body with Dyneema®, these gloves offer great cut resistance for a glove of such high dexterity and flexibility. A good choice for handling oily sharp steel, glass or circuit boards, especially when lint and particulate contamination is a concern.

For more information on gloves made with Dyneema® click the following link: http://www.superiorglove.com/work-gloves/cut-resistantgloves/dyneema-cut-resistant-gloves

Dyneema® is a registered trademark of Royal DSM N.V.

ASTM ANSI PUNCTURE 5 | ASTM ANSI ABRASION 4 | ASTM ANSI CUT LEVEL 2 | CE EN388 4342

558 grams of cut protection.

FEATURES

- ASTM cut-level 2 and CE-level 3 protection
- Great wet grip especially in oil
- Lint-free continuous filament yarn
- High dexterity and flexibility

APPLICATIONS

Sharp Steel
Glass
Circuit Boards
Automotive

AVAILABLE SIZES

6 7 8 9 10 11 12

Superior TOUCH®

Canadian Office and Factory
Acton, ON Canada
1-800-265-7617 | customerservice@superiorglove.com

US Warehouse
Buffalo, NY USA

European Office and Warehouse
Milano, Italy
0039 02 48841819 | sales.europe@superiorglove.com

superiorglove.com

SUPERIOR® GLOVE WORKS LTD.

Engineered hand protection for every industry®