Calibration Equipment (Group A)

- *GasAlertClip Extreme*
- *GasAlert Extreme*
- *GasAlertMicroClip XT*
- *GasAlertQuattro*
- *IQ Force™*
- *GasAlertMax XT II*
- *GasAlertMicro 5 Series*

Test Gases *Note: Not compatible with IQ Force.*	**Cylinder Material**	**Balance**	**Liters**	**Order Number**
Bump alarm test gas aerosol H_2S (25 ppm)	Aluminum	N_2	11	CG-BUMP-H25
Bump alarm test gas aerosol CO (100 ppm)	Aluminum	N_2	11	CG-BUMP-M100
Bump alarm test gas aerosol H_2S (40 ppm), CO (200 ppm), CH_4 (2.5%), O_2 (10%)	Aluminum	N_2	11	CG-BUMP1
Spare balloon assembly kit with hose (1/8 in. I.D., 3/16 in. O.D.) and adaptor for bump gas	-	-	-	CG-BUMP-B-K
Spare balloons for bump gas (kit of 10)	-	-	-	CG-BUMP-B

Note: Test gases are used for qualitative functional testing of sensors and alarms only. Test gases cannot be used as calibration gases.

Calibration Hoses *Note: Not compatible with IQ Force. See IQ Force product pages for hose options.*	**Order Number**
Calibration hose, Tygon (1 ft. / 0.3 m, 1/8 in. I.D., 1/4 in. O.D.)	C2-HOSE1-1
Calibration hose, Tygon (5 ft. / 1.5 m, 1/8 in. I.D., 1/4 in. O.D.)	C2-HOSE1-5
Calibration hose, Tygon (10 ft. / 3 m, 1/8 in. I.D., 1/4 in. O.D.)	C2-HOSE1-10
Connector fitting for Teflon®-lined hose (C2-HOSE4-1)	C2-CF-HOSE4

Regulators and Accessories	**Order Number**
Calibration gas regulator (0.5 LPM)	REG-0.5
Calibration gas regulator (0.5 LPM)	REG2-0.5
Calibration gas regulator (1.0 LPM)	REG-1.0
Demand flow regulator for disposable cylinders	REG-DF-1
Demand flow regulator for refillable cylinders, CGA connector	REG-DF-2
Demand flow regulator for disposable steel cylinders	REG-DF-3
Recycle kit for calibration gas cylinders	CG-RK-1
Wall mount (adjustable) for 34, 58, 103 L gas cylinders, red	MK-CG2-58
58 L or 34 L calibration cylinder blue carrying case	CK2-CASE1

Note: MicroDock II requires a REG-DF-1. Aerosols do not require regulators.