

Ground Fault Products

2 Pole 3 Wire Grounding**Straight Blade Automatic and Manual Set Portable GFCI Line Cords****Circuit Guard® Manual Set GFCI Line Cord**

All glass circuit board provides superior moisture immunity.

High impact UV stabilized housing resists dust, sunlight and chemicals for long life.

Heavy-duty molded plug and connector for reliable connection.

One-piece flush sealed keypads for greater reliability and resistance to damage due to impact.

Solid (not formed) plug blades are crimped and soldered for a better connection and longer life.

Bright fault indicator light provides fault confirmation from a distance.

Watertight GFCI housing for use in harsh environments.

Heavy-duty molded strain relief prevents conductor strain and resulting failure.

Available in Manual or Automatic Set.

**GFP4C15M**

Portable GFCI Line Cords provide ground fault protection both indoors and out. They interrupt electrical power for equipment loads when leakage to ground is 4-6 milliamperes. Available in lengths

of 18" (45.7 cm), 6' (182.9 cm), and 25' (762 cm). A 15' (457.2 cm) OEM version with stripped leads is also available. They are offered with an Automatic Set or Manual Set feature to meet your application.

Ground Fault Products

2 Pole 3 Wire Grounding

Industrial Grade, Straight Blade Automatic and Manual Set Portable GFCI Line Cords

Twist-Lock® Manual Set Portable GFCI Line Cords



IP21
SUITABILITY



Circuit Guard® Automatic Set Portable GFCI Line Cords

**15A
120V AC**

Description	Catalog Numbers
18" (45.7 cm) GFCI line cord.	GFP4C15A
6' (182.9 cm) GFCI line cord.	GFP6C15A
25' (762 cm) GFCI line cord.	GFP25C15A
15' (457.2 cm) GFCI power supply cord with stripped leads.	GFPOEMA*

Circuit Guard Manual Set Portable GFCI Line Cords

**15A 20A
120V AC 120V AC**

Description	Catalog Numbers
18" (45.7 cm) GFCI line cord.	GFP4C15M -
3' (91.4 cm) GFCI line cord.	- GFP3C20M
6' (182.9 cm) GFCI line cord.	GFP6C15M -
25' (762 cm) GFCI line cord.	GFP25C15M -
15' (457.2 cm) GFCI power supply cord with stripped leads.	GFPOEMM* -
50' (1524 cm) GFCI power supply with Elastogrip® watertight straight blade.	GFP50C15WM
100' (3048 cm) GFCI power supply with Elastogrip watertight straight blade.	GFP100C15WM

*Total length is 15' 4.5" (468.6 cm) including leads: green 4.5" (114.3), black and white 3.5" (88.9). Each prestripped .375" (9.5).

Circuit Guard Manual Set Twist-Lock Portable GFCI Line Cords

**15A 20A
120V AC 120V AC**

Description	Catalog Numbers
3' (91.4 cm) GFCI line cord.	GFP3C15MTL GFP3C20MTL

Automatic Set GFCI

Automatically energizes or sets the GFCI for use upon plug in and after the loss of primary power (power failure or unplugging the device). After a ground fault condition, unit must be reset by pushing the reset button. This feature eliminates the need for unit to be reset each time it is plugged in or powered up. Ideal for equipment intended for continuous use where a temporary power failure is likely and undesirable. Examples are pumps, pressure washers, portable signs or lighting and engine heaters.

Manual Set GFCI

Requires the GFCI to be manually set for use by pressing the reset button upon plug in and after loss of primary power (power failure or unplugging the device). Must be manually reset after a ground fault condition. Ideal for applications where operator injury might occur if equipment were to restart after a power failure. Typical equipment includes power drills, saws, lathes and grinders.

Specifications

Portable GFCI Line Cords

Trip Level	4 to 6 mA.
Trip Time	.025 sec. nominal.
Frequency	60 Hz.
Voltage	120V AC +10% - 15%. Incorporates no voltage release feature.
Current	15A/20A.
Maximum Interrupting Capacity	2000A.
Operating Temperature	-35°C to +66°C or -30°F to +150°F.
Maximum Humidity	95%.
Housing	High-impact, UV stabilized PVC. UL 94V-0 flammability classification. Meets UL and CSA watertight requirements. Adhesive bonded.
Cord Type	SJTW-A (UL), SJTW (CSA).
Visual Fault Indication Light On Listing and Standards	Indicates fault. Meets UL943 2003 Class A UL File E41978 CSA Certified.
Code	Meets all NEC & CEC requirements.



GFP4C15A



GFP3C20M



GFPOEMM



GFP3C20MTL

Straight Blade

Input 15A NEMA 5-15P, 20A NEMA 5-20P.
Output 15A NEMA 5-15R (except GFPOEMM), 20A NEMA 5-20R.

Twist-Lock®

Input 15A NEMA L5-15P HBL47CM20C, 20A NEMA L5-20P HBL23CM11.
Output 15A NEMA L5-15R HBL47CM29C, 20A NEMA L5-20R HBL23CM13.

