Other Wiring Products

Adapters



Nylon Convenience Adapters



HBI 52731



HBL5289

| NEMA Configuration | | | | | |
|-------------------------|--------------|-------------------------|-------------------------|-------------------------|--|
| Male Blade End | W | 15A 125V NEMA L5-15P | 20A 125V NEMA L5-20P | 30A 125V NEMA L5-30P | |
| Female Slot End | Catalog Numb | er | | | |
| 20A 125V NEMA 5-20R | HBL2270 | HBL2274 | HBL2129 | HBL31CM29* | |
| 15A 125V NEMA L5-15R | HBL2271 | - | _ | - | |
| 20A 125V NEMA L5-20R | HBL2128 | - | _ | - | |

Caution:



9053A

- Where adapters have different ratings on the blade and slot end the following precautions must be exercised in their use.
- (1) Remember that overcurrent protection is determined by the blade end.
- (2) The use of the adapter should be limited to the lowest rated end of the adapter in order to prevent overheating.
- (3) Adapters do not provide GFCI, overcurrent or short circuit protection.



9054A

Plug In Adapters

| Description | Catalog Number |
|---|----------------|
| Male end - 2 wire parallel polarized blades, 15A, 125V. Female end - 3 wire 15A, 125V straight slot grounding. | HBL5273L |
| Male end - 3 wire crow foot 15A, 125V blades. Female end - 3 wire 15A, 125V straight slot grounding. | HBL5289 |
| Male end - 3 wire 10A, 250V, 15A, 125V Twist-Lock® blades. Female end - 3 wire 15A, 125V straight slot grounding. | 9053A◆* |
| Male end - 3 wire 15A, 125V straight blade grounding. Female end - 10A, 250V, 15A 125V Twist-Lock® slots. | 9054A◆* |

- ♦ Must always be used with a grounded receptacle.
- * Not UL Listed.

