

Wall Plates Selection Charts




Wall Plates for Single Receptacles

Description	Group A		Group B		Group C		Group D		Group E
	One Gang	Two Gang	One Gang	Two Gang	One Gang	Two Gang	One Gang	Two Gang	Two Gang
	Boss diameter 1.36" to 1.39" (34.5 to 35.3)		Boss diameter 1.55" to 1.58" (39.4 to 40.1)		Boss diameter 1.68" to 1.72" (42.7 to 43.7)		Boss diameter 2.09" to 2.13" (53.1 to 54.1)		Boss diameter 2.28" to 2.44" (57.9 to 62.0)
	Catalog Numbers								
Smooth nylon, ivory.	P7	-	P720	-	-	-	P724	P703	-
Smooth nylon, brown.	P7X	-	P720X	-	-	-	P724X	P703X	-
Smooth nylon, black.	P7B	-	P720B	-	-	-	P724B	P703B	-
Cast aluminum.	HBL7320	-	HBL7320	-	HBL3394	-	HBL9419	-	-
Stainless steel, 302/304, smooth.	S7	-	S720	-	S725	-	S723	S703	S701
Anodized aluminum, smooth metal.	A7	-	-	-	-	-	A723	-	-
Solid brass, smooth metal.	B7	-	B720	-	-	-	-	-	B701

See appropriate catalog page for complete description of plate.

Catalog Numbers of Receptacles in Groups A thru E Above

Group A	Group B	Group C	Group D	Group E
HBL7310B	HBL5661	HBL23CM10	HBL26CM10	HBL2820
HBL7310BG	HBL6810	HBL2310	HBL2610	HBL2830
HBL23000HG	HBL7210B	HBL2320	HBL2620	HBL3330
HBL23030	HBL7250	HBL2330	HBL2630	HBL3330G
HBL4560	HBL7310B	HBL2340	HBL2640	HBL3430
HBL4710	HBL7310BG	HBL2410	HBL2650	HBL3430G
HBL4760	HBL7535	HBL2420	HBL2710	HBL3520
HBL5251	HBL7582	HBL2430	HBL2720	HBL7410B
HBL52CM61	HBL8310	HBL2440	HBL2730	HBL7410BG
HBL5261	HBL8410	HBL2450	HBL2740	
HBL53CM61	HBL8420	HBL2460	HBL2750	
HBL5361		HBL2510	HBL2760	
HBL5461		HBL2520	HBL2770	
HBL5552B		HBL2530	HBL2810	



Weatherproof Lift Cover Plates for WDL "Closed" and WDL "Open," Single Gang

	Group A	Group B	Group C	Group D	50A Twist-Lock® Receptacles	30A, 4W Hubbell® Receptacles
	Boss diameter 1.36" to 1.39" (34.5 to 35.3)	Boss diameter 1.55" to 1.58" (39.4 to 40.1)	Boss diameter 1.68" to 1.72" (42.7 to 43.7)	Boss diameter 2.09" to 2.13" (53.1 to 54.1)		
Thermoplastic, WET LOCATIONS with cover "open," gray.	HBL7423WO	HBL7425WOA	HBL7424WO	-	HBL7774WO▲	-
Thermoplastic, WET LOCATIONS with cover "open," yellow.	HBL74CM23WO	HBL74CM25WOA	HBL74CM24WO	-	HBL77CM74WO▲	-
Cast aluminum, WET LOCATIONS with cover "closed".	-	HBL7420	HBL3393	HBL9420	HBL7770	HBL20405 HBL20446*

▲ The "CS" versions of 50A Twist-Lock® receptacles will only fit these thermoplastic plates.

*Plate painted red for Cat. HBL20443 only. Cat. No. HBL20405 plate for Cat. No. HBL20403 only.

Wall Plates

Weatherproof Plates for Receptacles and Switches

Vertical, for FS/FD box mounting



HBL7423WO



HBL7425WOA



HBL7424WO



HBL7420



HBL7320



HBL3393


IP44
SUITABILITY
For Receptacles With Face Diameters of 1.36"-1.39" (34.5-35.3)

Description	Catalog Numbers
Thermoplastic, WET LOCATIONS with cover "open," gray.	HBL7423WO
Thermoplastic, WET LOCATIONS with cover "open," yellow.	HBL74CM23WO
Cast aluminum, WET LOCATIONS with cover "closed."	HBL7420▲

For Receptacles With Face Diameters of 1.55"-1.58" (39.4-40.1)

Description	Catalog Numbers
Thermoplastic, WET LOCATIONS with cover "open," gray.	HBL7425WOA
Thermoplastic, WET LOCATIONS with cover "open," yellow.	HBL74CM25WOA
Cast aluminum, WET LOCATIONS with cover "closed."	HBL7420▲
Cast aluminum, no lift cover, NOT weatherproof.	HBL7320

For Receptacles With Face Diameters of 1.68"-1.72" (42.7-43.7)

Description	Catalog Numbers
Thermoplastic, WET LOCATIONS with cover "open," gray.	HBL7424WO
Thermoplastic, WET LOCATIONS with cover "open," yellow.	HBL74CM24WO
Cast aluminum, WET LOCATIONS with cover "closed."	HBL3393
Cast aluminum, no lift cover, NOT weatherproof.	HBL3394

▲ A fiber shield is furnished with HBL7420 plate. An effective means of weatherproofing toggle and lock type switches when this shield is used in combination with the plate.

All weatherproof lift cover plates on this page are listed by Underwriters Laboratories, Inc. as "WDL Closed" for use in wet locations with cover closed and in damp locations.

Weatherproof Covers For Single Receptacles On FS/FD Boxes

Note: All weatherproof plates are UL Listed for WET LOCATIONS WITH COVER CLOSED, for intermittent use in wet locations or use in damp locations. Those with suffix WO are listed for WET LOCATIONS with cover open in continuous use. All plates are gasketed and self-closing.

National Electrical Code**Receptacles in Damp or Wet Locations.**

(a) **Damp Locations.** A receptacle installed outdoors in a location protected from the weather or in other damp locations shall have an enclosure for the receptacle that is weatherproof when the receptacle is covered (attachment plug cap not inserted and receptacle covers closed).

An installation suitable for wet locations shall also be considered suitable for damp locations.

A receptacle shall be considered to be in a location protected from the weather where located under roofed open porches, canopies, marquees, and the like, and will not be subjected to a beating rain or water run-off.

(b) Wet Locations.

(1) A receptacle installed in a wet location where the product intended to be plugged into it is not attended while in use (e.g., sprinkler system controllers, landscape lighting, holiday lights, etc.) shall have an enclosure that is weatherproof with the attachment plug cap inserted or removed.

(2) A receptacle installed in a wet location where the product intended to be plugged into it will be attended while in use (e.g., portable tools, etc.) shall have an enclosure that is weatherproof when the attachment plug cap is removed.