

# Switched Enclosures

## Circuit-Lock® Unfused Disconnect Switches

“Suitable as Motor Disconnect”



UL Listed, CSA Certified  
TYPE 4, 4X and  
12 Enclosure Rating

**IP66**  
SUITABILITY

### 30, 60 and 100 Amp Unfused Disconnect Switches

Description	Catalog Number
30A Circuit-Lock disconnect switch.	HBLDS3
30A Circuit-Lock disconnect switch for use with variable frequency drives.	HBLDS3VFD <sup>A</sup>
30A Circuit-Lock disconnect switch with HBLAC1 aux. contact.	HBLDS3AC
30A Circuit-Lock disconnect switch with HBLAC2 aux. contact.	HBLDS3AC2
30A Circuit-Lock disconnect switch without conduit knockout or conduit fitting.	HBLDS3NK
30A Circuit-Lock disconnect switch with HBLAC1 aux. contact without conduit knockout or conduit fitting.	HBLDS3ACNK
30A Circuit-Lock disconnect switch with 3 aux. contacts, w/o conduit knockouts. Break before main break – 1 set “normally open”, 1 set “normally closed”. Break after main break – 2 sets “normally open”, 1 set “normally closed”.	HBLDS33ACNK
60A Circuit-Lock disconnect switch.	HBLDS6
60A Circuit-Lock disconnect switch with HBLAC1 aux. contact.	HBLDS6AC
100A Circuit-Lock disconnect switch.	HBLDS10
100A Circuit-Lock disconnect switch with HBLAC1 aux. contact.	HBLDS10AC



HBLDS3AC



HBLAC1



HBLAC2

### Auxiliary Contacts for 30, 60 and 100 Amp Switch, A600 Pilot Duty

Description	Catalog Number
“Break After Main Break”, 1 set of n/o contacts, 1 set of n/c contacts.	HBLAC1*
“Break Before Main Break”, 1 set of n/o contacts.	HBLAC2*

### Ground Block

Description	Catalog Number
For 30A switches.	HBL30RGB
For 60A and 100A switches.	HBL60100RGB

### Neutral Block

Description	Catalog Number
For 30A switches.	HBL30RNB
For 60A switches.	HBL60RNB
For 100A switches.	HBL100RNB

Note: \* Not for use with HBLDS33ACNK.

30A Units are supplied with one 3/4 in. N.P.T. Raintight conduit fitting.

60A and 100A Units are supplied with two 1 1/4 in. N.P.T. Raintight conduit fittings.

<sup>A</sup> See page C-34 for wiring details.



HBL30RGB



HBL30RNB