

Straight Blade Devices

2 Pole, 3 Wire Grounding

15 and 20 Ampere, 125 Volts

Heavy Duty, Specification Grade and Hospital Grade Single Receptacles




NEMA 5-15R
15A 125V
UL CSA
0.5 HP



NEMA 5-20R
20A 125V
UL Listed
1 HP


Heavy Duty, Specification Grade, Single Receptacles

Description	Color	Catalog Numbers	
Flush, nylon face, back and side wired.	Brown	HBL5261	HBL5361
	Ivory	HBL5261I	HBL5361I
	Gray	-	HBL5361GRY
Flush, nylon face, back and side wired.	Brown	HBL5261CN*	-
	Ivory	HBL5261ICN*	-




Special Purpose Single Receptacles

Description	Color	Catalog Numbers	
Corrosion resistant.	Yellow	HBL52CM61	HBL53CM61
On a 4" (101.6) round cover.	Brown	HBL5281	-
Isolated ground.	Orange	IG5261	IG5361
	Orange	IG5261CN*	-
Panel mount on 1.94" (49.3) centers.	Brown	HBL5284	HBL5357



Heavy Duty, Hospital Grade, Single Receptacles

Description	Color	Catalog Numbers	
Flush, nylon face, back and side wired. ⁽¹⁾ HBL8310	Brown	HBL8210	HBL8310
	Ivory	HBL8210I	HBL8310I
	Gray	HBL8210GY	HBL8310GY
	Red	HBL8210R	HBL8310R
	White	HBL8210W	HBL8310W
Isolated ground. ⁽²⁾	Orange	IG8210	IG8310
Panel mount on 1.94" (49.3) centers.	Brown	HBL8284	-
	Ivory	HBL8284I	HBL8384I





Notes: *Catalog numbers listed above with suffix CN have combination Robertson/slotted head terminal and mounting screws. All others have slotted screws.



5-20R
Canadian
20A 125V
UL CSA
1 HP

Heavy Duty, Specification Grade, Single Receptacles—Robertson/slotted screws

Description	Color	Catalog Numbers	
Flush, nylon face, back and side wired.	Brown	HBL6331CN	HBL6331CN
	Ivory	HBL6331ICN	HBL6331ICN
Heavy duty hospital grade.	Brown	HBL8310CN	HBL8310ICN



Horsepower ratings listed above are AC only.

⁽¹⁾See Section H for complete line of hospital grade devices.

⁽²⁾See Section G for complete line of Circuit Guard[®] isolated ground devices.