

## Wire Rope Splicing Grips

Triple, Double, Single Weave, Galvanized Steel



### WARNING!

It is important that you read all breaking strength, safety and technical data relating to this product on pages T-17 through T-27.

### Regular Wire Rope Grips

Cable Diameter Range Inches (cm)	Approx. Breaking Strength Lbs. (N)	Approx. Length Of Grip Feet (m)	Catalog Numbers
9/16" - 5/8" (1.43-1.59)	7,500 (33,360)	5.75 (1.75)	<b>03316001</b>
3/4" - 7/8" (1.90-2.22)	12,500 (55,600)	6.75 (1.90)	<b>03316002</b>
1" - 1 1/8" (2.54-2.86)	16,000 (71,168)	7.00 (2.13)	<b>03316003</b>
1 1/4" - 1 3/8" (3.17-3.49)	20,000 (88,960)	8.00 (2.44)	<b>03316004</b>
1 3/8" - 1 1/2" (3.49-3.81)	20,000 (88,960)	8.00 (2.44)	<b>03316006</b>

Kellems® Wire Rope Grips are made of high strength galvanized steel strand in a construction of triple, double and single weave for superior gripping ability. They are available with or without a rotating barrel which will help eliminate twist in the old rope from being transferred to the new rope.



### Rotating Wire Rope Grips

Cable Diameter Range (cm)	Approx. Breaking Strength Lbs. (N)	Approx. Length Of Grip Feet (m)	Barrel Dimensions Lgth. x O.D. In. (cm)	Catalog Numbers
7/16" - 1/2" (1.11-1.27)	5,000 (22,240)	5.33 (1.63)	3.00" (7.62) x .87" (2.21)	<b>03317001</b>
9/16" - 5/8" (1.43-1.59)	7,500 (33,360)	5.83 (1.78)	4.25" (10.79) x 1.00" (2.54)	<b>03317002</b>
3/4" - 7/8" (1.90-2.22)	12,500 (55,600)	6.50 (1.98)	4.25" (10.79) x 1.00" (2.54)	<b>03317003</b>
1" - 1 1/8" (2.54-2.86)	16,000 (71,168)	8.67 (2.64)	5.50" (13.97) x 1.37" (3.48)	<b>03317004</b>
1 1/4" - 1 3/8" (3.17-3.49)	20,000 (88,960)	9.00 (2.74)	5.50" (13.97) x 1.37" (3.48)	<b>03317005</b>
1 1/2" - 1 3/4" (3.81-4.44)	20,000 (88,960)	11.00 (3.35)	5.50" (13.97) x 1.37" (3.48)	<b>03317006</b>