

# Dust-Tight Strain Relief Grips

Aluminum Fittings, Galvanized Steel Mesh, for Insulated Cables



### WARNING!

It is important that you read all breaking strength, safety and technical data relating to this product on pages T-71 through T-76.

### Non-Insulated, Wide Range Strain Relief

Cable Diameter Range Inches (cm)	Thread Size	Mesh Length @ Nom. Dia. Inches (cm)	Catalog Numbers
.24"-.32" (.61-.81)	½ N.P.T.	3.25" (8.25)	073031200
.32"-.43" (.81-1.09)	½ N.P.T.	3.75" (9.52)	073031201
.43"-.54" (1.09-1.37)	½ N.P.T.	4.75" (12.06)	073031202
.54"-.73" (1.37-1.85)	¾ N.P.T.	6.5" (16.51)	073031203
.73"-.97" (1.85-2.46)	1 N.P.T.	7" (17.78)	073031204
.97"-1.25" (2.46-3.17)	1¼ N.P.T.	9" (22.86)	073031205
.73"-.97" (1.85-2.46)	PG29*	7" (17.78)	073PG291204

\* Panzergewinde



Non-Insulated

### Insulated, Wide Range Strain Relief with Insulating Bushing

Cable Diameter Range Inches (cm)	Thread Size	Mesh Length @ Nom. Dia. Inches (cm)	Dim. A In. (cm)	Min. Space Between Grips In. (cm)	Catalog Numbers
.24"-.32" (.61-.81)	½ N.P.S.	3.25" (8.25)	1" (2.54)	1.25" (3.17)	073031206
.32"-.43" (.81-1.09)	½ N.P.S.	3.75" (9.52)	1" (2.54)	1.25" (3.17)	073031207
.43"-.54" (1.09-1.37)	½ N.P.S.	4.75" (12.06)	1" (2.54)	1.25" (3.17)	073031208
.54"-.73" (1.37-1.85)	¾ N.P.S.	6.5" (16.51)	1" (2.54)	1.5" (3.81)	073031209
.73"-.97" (1.85-2.46)	1 N.P.S.	7" (17.78)	1.313" (3.02)	1.75" (4.44)	073031210
.97"-1.25" (2.46-3.17)	1¼ N.P.S.	9" (22.86)	1.313" (3.02)	2.25" (5.71)	073031211
1.25"-1.50" (3.17-3.81)	1½ N.P.T.	11.75" (29.84)	1.313" (3.02)	2.5" (6.35)	073031212
1.50"-1.70" (3.81-4.32)	2 N.P.T.	13.25" (33.65)	1.375" (3.49)	3.25" (8.25)	073031213
1.70"-2.00" (4.32-5.08)	2½ N.P.T.	13.5" (34.29)	1.5" (3.81)	3.625" (9.21)	073031214
2.00"-2.45" (5.08-6.22)	2½ N.P.T.	13.75" (34.92)	1.5" (3.81)	3.625" (9.21)	073031215



Insulated

