






## Flush Duplex FRPT 3" Diameter – One Piece Units



Catalog Number			Catalog Number		
<b>PT7FSDBLA</b>	Black	<b>Flush Aluminum Poke-Through</b>	<b>PT7FSDBRS2A</b>	All Brass	<b>Flush Brass Poke-Through</b>
<b>PT7FSDGYA</b>	Gray		<b>PT7FSDBRS3A</b>	Black/Brass	
<b>PT7FSDIA</b>	Ivory		<b>PT7IGFSDBRSA*</b>	All Brass	
<b>PT7FSDBRA</b>	Brown		* Includes pre-wired 20A isolated ground duplex receptacle.		
<b>PT7IGFSDGYA*</b>	Gray		Complete assembled unit		
<b>PT7IGFSDIA*</b>	Ivory		<ul style="list-style-type: none"> <li>■ <b>PT7FSD</b> through-floor fitting.</li> <li>■ Pre-wired 20A duplex receptacle.</li> <li>■ Non-metallic flip lid cover with (2) 1/2" diameter low voltage feed through holes.</li> <li>■ Painted aluminum flange.</li> </ul>		
* Includes pre-wired 20A isolated ground duplex receptacle.			* Includes pre-wired 20A isolated ground duplex receptacle.		
Complete assembled unit			Complete assembled unit		
<ul style="list-style-type: none"> <li>■ <b>PT7FSD</b> through-floor fitting.</li> <li>■ Pre-wired 20A duplex receptacle.</li> <li>■ Non-metallic flip lid cover with (2) 1/2" diameter low voltage feed through holes.</li> <li>■ Painted aluminum flange.</li> </ul>			<ul style="list-style-type: none"> <li>■ <b>PT7FSD</b> through-floor fitting.</li> <li>■ Pre-wired 20A duplex receptacle.</li> <li>■ All brass or black non-metallic cover option.</li> <li>■ Flip lid cover with (2) 1/2" diameter low voltage feed through holes.</li> <li>■ Solid brass flange.</li> </ul>		

## Flush FRPT 3" Diameter – Two Piece Units

### Through-Floor Fitting

Catalog Number			Catalog Number		
<b>PT7FSD</b> (with Junction Box)		<b>Multi-Channel Through Floor Fitting</b>			
<b>PT73SD</b> (without Junction Box)					
Through-floor fitting with (1) 3/4" trade size conduit stem for power and (2) 1/2" low voltage feed through holes.			Specifications:		
			<ul style="list-style-type: none"> <li>■ UL Listed and CSA Certified.</li> <li>■ 1 - 4 hour fire rating (1- 3 hour for steel floor units and concrete topping, D900 Series Design).</li> <li>■ For 2 1/4" to 7" floor thickness.</li> <li>■ UL installation spacing. Minimum 2 ft. on center and not more than 1 per 65 sq. ft. of floor area.</li> </ul>		

### Service Fittings

Catalog Number			Catalog Number		
<b>FRFBLA</b>	Black	<b>Flush Aluminum Service Fitting</b>	<b>FRFBRS2A</b>	Solid Brass	<b>Flush Brass Service Fitting</b>
<b>FRFGYA</b>	Gray				
<b>FRFIA</b>	Ivory				
<b>FRFBRA</b>	Brown				
<ul style="list-style-type: none"> <li>■ Pre-wired 20A duplex receptacle.</li> <li>■ Non-metallic flip lid cover with (2) 1/2" diameter low voltage feed-through holes.</li> <li>■ Painted aluminum flange.</li> </ul>			<ul style="list-style-type: none"> <li>■ Pre-wired 20A duplex receptacle.</li> <li>■ Solid brass flip lid cover with (2) 1/2" diameter low voltage feed-through holes.</li> <li>■ Solid brass flange.</li> </ul>		

### Accessories

Catalog Number			Catalog Number		
<b>PFBRCBLA</b>	Black	<b>Non-Metallic Replacement Covers</b>	<b>BRS2RCA</b>	Solid Brass	<b>All Brass Replacement Covers</b>
<b>PFBRCGYA</b>	Gray				
<b>PFBRCIA</b>	Ivory				
<b>PFBRCBRA</b>	Brown				
		