







Large Capacity, Low Voltage Flush Furniture Feed FRPT 3" Diameter – Two Piece Units



Catalog Number		Catalog Number		
PT2FIT	Large Capacity, Low Voltage Through Floor Fitting	FF2BRS	Brass Finish	Large Capacity Cover/Flange
		FF2BK	Black	
		FF2GY	Gray	
<p>Through floor fitting with (1) 2" trade size conduit stem. Will accommodate up to 36 Category 5e cables.</p> <p>Specifications:</p> <ul style="list-style-type: none"> ■ UL Listed and CSA Certified. ■ 1-2 hour fire rating. ■ For 2 1/4" to 7" floor thickness. ■ UL installation spacing. Minimum 2 ft on center and not more than 1 per 65 sq. ft. of floor area. 		<ul style="list-style-type: none"> ■ Cover/flange with 1 1/4" & 2" combination knockout. ■ Painted aluminum cover and flange. 		
				

Flush Furniture Feed FRPT 3" Diameter – One Piece Units

Catalog Number		Catalog Number		
PT73FFSDGY	Gray	PT7FFSDGY	Gray	Single Service Furniture Feed Poke-Through
PT73FFSDI	Ivory	PT7FFSDI	Ivory	
<p>3 Service Furniture Feed Poke-Through</p> <p>Complete assembled unit</p> <ul style="list-style-type: none"> ■ PT73SD floor fitting. ■ Aluminum cover with (2) 1/2" threaded hubs for low voltage and (1) 3/4" threaded hub for power. ■ Painted aluminum flange. 		<p>Single Service Furniture Feed Poke-Through</p> <p>Complete assembled unit</p> <ul style="list-style-type: none"> ■ PT71SD floor fitting. ■ Aluminum cover with (1) KO to accept a 3/4" connector. ■ Painted aluminum flange. 		
				

Flush Furniture Feed FRPT 3" Diameter – Two Piece Units

Through-Floor Fittings

Catalog Number		Catalog Number		
PT73SD	3 Service Furniture Feed Through-Floor Fitting	PT71SD	Single Service Furniture Feed Through-Floor Fitting	
<p>Through-floor fitting with (1) 3/4" trade size conduit stem for power and (2) 1/2" low voltage conduit holes.</p> <p>Specifications:</p> <ul style="list-style-type: none"> ■ UL Listed and CSA Certified. ■ 1- 4 hour fire rating (1-3 hour for steel floor units and concrete topping, D900 Series Design). 		<p>Through-floor fitting with (1) 3/4" trade size conduit stem for power or low voltage applications.</p> <ul style="list-style-type: none"> ■ For 2 1/4" to 7" floor thickness. ■ UL installation spacing. Minimum 2 ft. on center and not more than 1 per 65 sq. ft. of floor area. 		
				

Service Fittings

Catalog Number		Catalog Number		
FRF3BK	Black	FRF1BK	Black	Single Service Furniture Feed Service Fitting
FRF3GY	Gray	FRF1GY	Gray	
FRF3I	Ivory	FRF1BRS	Brass Finish	
<p>3 Service Furniture Feed Service Fitting</p> <ul style="list-style-type: none"> ■ Aluminum cover with (2) 1/2" threaded hubs for low voltage and (1) 3/4" threaded hub for power. ■ Painted aluminum flange. 		<ul style="list-style-type: none"> ■ Aluminum cover with (1) KO to accept a 3/4" connector. ■ Painted aluminum flange. 		