












Through-Floor Fitting

Description	Catalog No.
Large Capacity Multi-Service Pedestal Through-Floor Fitting with (1) 1 ¼ in. E.M.T. stem for low voltage and (1) ½ in. E.M.T. stem for power applications. Specifications: <ul style="list-style-type: none"> 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design). For 2¼ in. to 7 in. floor thickness. Approved for use in the City of Chicago. 	PT7XC 

Pedestal Service Fitting

Description	Color/Material	Catalog No.
2-Gang Pedestal Service Fitting For use with PT7XC only. Specifications: <ul style="list-style-type: none"> Brushed aluminum housing with low voltage barrier. Plates and devices sold separately. 	Brushed Aluminum	FR80AL 

3-Inch Core Hole FRPT Accessories

Description	Color	Catalog No.	Description	Color/Gang	Catalog No.
Closure Plug Textured aluminum plug seals 3 in. core hole when FRPT is no longer required and is removed. Maintains the floor's 1 – 4 hour fire rating. UL Listed and CSA Certified.	Gray	FRP250 	PT7XC Extension Kit Extends PT7XC FRPT to accommodate between 7 in. and 13 in. floor thickness.	—	EXT13 
Flush FRPT Abandonment Plate Use with PT7FSD, PT73SD or PT71SD only. Covers the opening when FRPT is abandoned. Service fitting is removed and through-floor fitting remains.	Gray Ivory	AP2GY AP2I 	Pedestal FRPT Abandonment Plate Use with PT27A or PT7XC only. Covers the opening when FRPT is abandoned. Service fitting is removed and through-floor fitting remains.	Gray/2-gang	AP22  Gray/2-gang AP42 
Multi-Service Furniture Feed Replacement Inserts Use as a replacement cover for PT73FFSD series, or to convert installed PT7FSD series into furniture feed FRPTs. Includes (2) ½ in. threaded hubs for low voltage and (1) ¾ in. threaded hub for power. (UL Listed only.)	Gray Ivory	FF3GY FF3I 	Replacement Low Voltage Barrier Use with FR280, FR480, and FR680 pedestal service fittings only when additional power/low voltage separation is required.	—	FRBR1 

Plates

Description	Catalog No.	Description	Catalog No.
Duplex 	SS309D	Furniture Feed (¾ in. KO) 	SS309SF*
Style Line®/ GFCI 	SS309DS	Furniture Feed Blank 	SS309BF*
Single Rec. (1.39 in. OD) 	SS309S	Bushed Data Opening (1 in. ID) 	SS309T
Blank 	SS309B	<ul style="list-style-type: none"> 302/304 Stainless Steel plates (SS309SF & SS309BF are Aluminum). UL Listed and CSA Certified. 	

Note: *For furniture feed applications using **SS309SF**, a **SS309BF** blank must be used for second plate.



Complies with UL514 A & C

