

HBL500 and HBL750 Series	<b>U</b> L LISTED	© CERTIF
Fittings	HBL500 & HBL750 Series C	olor
Support Clip For supporting lengths of HBL500 or HBL750 Raceway.		vory Vhite
Elbow Box Connector For connecting raceway at right angles to conduit boxes, panel boxes, etc. having KO for trade size conduit.	HBL5783IV Iv A: 2.13" (54.05) B: 1.24" (31.50)	ory
Elbow Conduit Connector For connecting raceway at right angles to ½ in. trade size conduit or armored cable connectors.	HBL5784IV (54.05) A: 2.13" (54.05) B: 1.24" (31.50)	vory
Combination Connector For connecting raceway, without offsetting, to any 3.25 in. (83.00) or 4 in. (102.00) outlet box mounted on the surface with a KO for ½ in. trade size conduit. Spring steel bushing (included) eliminates need for conduit nipple and locknut.		vory Vhite
Adjustable Offset Connector Two ½ in. KOs for panel or conduit connection. Eliminates offsetting raceway when connecting to surface type panel boxes. One ½ in.		vory Vhite

chase nipple and locknut furnished.





**Entrance Connector** One ¾ in. KO for panel or conduit connection. One ¾ in. chase nipple and locknut furnished.



HBL5786AIV HBL5786AW A: 1.50" (38.10) B: 1.84" (46.74) C: 3.89" (98.87) Ivory White

Flexible Section For getting around offsets, side bends, twisted turns or curved surfaces.





HBL5700FIV A: 18.00" (457.20) Ivory

1/2 in. EMT Connector

For connecting raceway to conduit boxes or panel boxes having KO for conduit.





HBL5791 A: 1.20" (30.48) B: 1.09" (27.70) Zinc Plated Steel