





# tradeSELECT® Products Range and Dryer Power Receptacles and Plugs

30 and 50 Ampere, 125/250 Volts AC, 3 Pole, 3 Wire and 3 Pole, 4 Wire



## Range and Dryer Power Receptacles

				
Description	Flush Mount for 1- or 2-Gang Box	Flush Mount for 1- or 2-Gang Box	Flush Mount for 1- or 2-Gang Box	Flush Mount for 1- or 2-Gang Box
Rating	30A 125/250V 3 Pole, 4 Wire with Ground	50A 125/250V 3 Pole, 4 Wire with Ground	30A 125/250V 3 Pole, 3 Wire without Ground	50A 125/250V 3 Pole, 3 Wire without Ground
Black	<b>RR430F</b>	<b>RR450F</b>	<b>RR330F*</b>	<b>RR350F*</b>
White	<b>RR430FW</b>	<b>RR450FW</b>	—	—
<hr/>				
Description	Surface Mount	Surface Mount	Surface Mount	Surface Mount
Rating	30A 125/250V 3 Pole, 4 Wire with Ground	50A 125/250V 3 Pole, 4 Wire with Ground	30A 125/250V 3 Pole, 3 Wire without Ground	50A 125/250V 3 Pole, 3 Wire without Ground
Black	<b>RR430</b>	<b>RR450</b>	<b>RR330*</b>	<b>RR350*</b>
<hr/>				
Description	Panel Mount	Panel Mount		
Rating	30A 125/250V 3 Pole, 4 Wire with Ground	50A 125/250V 3 Pole, 4 Wire with Ground		
Black	<b>RR430PM</b>	<b>RR450PM</b>		
White	—	—		

Note: \*For replacement use only.



RR430FW







RR450



RR430PM

## Range and Dryer Power Angled Plugs

				
Description	With Interchangeable Blades for 30 or 50 Amp		With Interchangeable Blades for 30 or 50 Amp	
Rating	30/50A 125/250V 3 Pole, 4 Wire with Ground		30/50A 125/250V 3 Pole, 3 Wire without Ground	
Black	<b>RR435P</b>		<b>RR335P</b>	



RR435P

## Wallplates, Surface Mount, 2.15" Diameter Single Hole

Description	1-Gang Standard	1-Gang Mid size	2-Gang Standard	2-Gang Mid size
Ivory	<b>NP724I</b>	<b>NPJ724I</b>	<b>NP703I</b>	<b>NPJ703I</b>
White	<b>NP724W</b>	<b>NPJ724W</b>	<b>NP703W</b>	<b>NPJ703W</b>
Chrome	<b>SCH723</b>	—	—	—
Stainless Steel	<b>SS723</b>	—	<b>SS703</b>	—



NP724W



NP703W