




**Features**

Standard toggle switches provide the basic on/off control for home lighting and appliances.

- Tough thermoplastic with ultrasonically welded cover and base
- Elongated strap for easier wall box mounting
- Hi-visibility yellow base for easy installation
- Operating temperature: -20°C to 60°C
- UL Listed E3896, CSA Certified




**RS115W**

**Features**

Mini-toggles provide for multiple switches in a compact single gang. Maximize control while maintaining function and appearance.






- Low profile, less than 1 inch
- Self-grounding feature is standard
- Smooth toggle action
- Operating temperature: -20°C to 60°C
- UL Listed, CSA Certified



**RC108I**









### Combination Toggle Switches/Devices

				
Description	Two (2) Single Pole Switches	Single Pole Switch, Tamper-Resistant, 2 Pole, 3 Wire, Receptacle	Single Pole Switch, 2 Pole, 3 Wire, Receptacle	Single Pole Switch, Pilot Light, Clear Lens, Amber Neon Bulb*
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 120V AC	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V AC
				
Color				
Brown	<b>RC101</b>	<b>RC108TR</b>	<b>RC108</b>	<b>RC109</b>
Ivory	<b>RC101I</b>	<b>RC108ITR</b>	<b>RC108I</b>	<b>RC109I</b>
Light Almond	<b>RC101LA</b>	<b>RC108LATR</b>	<b>RC108LA</b>	<b>RC109LA</b>
White	<b>RC101W</b>	<b>RC108WTR</b>	<b>RC108W</b>	<b>RC109W</b>

Note: See page Tech-10 for Tamper-Resistant description.  
 \*Neutral required for pilot light, see page X-4 for wiring diagram.

### Combination Toggle Switches/Devices

					
Description	Single Pole and Three Way Switch	Two (2) Three Way Switches	Three Way Switch, Tamper-Resistant, 2 Pole, 3 Wire, Receptacle	Three Way Switch, 2 Pole, 3 Wire, Receptacle	Three Way Switch, Pilot Light, Clear Lens, Amber Neon Bulb*
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 120V AC	15A 120V AC	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V AC
					
Color					
Brown	<b>RC103</b>	<b>RC303</b>	<b>RC308TR</b>	<b>RC308</b>	<b>RC309</b>
Ivory	<b>RC103I</b>	<b>RC303I</b>	<b>RC308ITR</b>	<b>RC308I</b>	<b>RC309I</b>
Light Almond	<b>RC103LA</b>	<b>RC303LA</b>	—	—	—
White	<b>RC103W</b>	<b>RC303W</b>	<b>RC308WTR</b>	<b>RC308W</b>	<b>RC309W</b>

Note: See page Tech-10 for Tamper-Resistant description.  
 \*Neutral required for pilot light, see page X-4 for wiring diagram.