



**Features**

- Low profile, less than 1 inch deep
- Self-grounding feature is standard
- Operating temperature: -20°C to 60°C
- UL Listed E3896, CSA Certified

**Combination Quiet Rocker Switches/Devices**



**RCD111W**



**RCD101W**





**RCD108W**



**RCD109W**



**DD100NLWH**

Description	Three (3) Single Pole Switches	Two (2) Single Pole Switches	Single Pole and Three Way Switch	 * Single Pole Switch, Tamper-Resistant, 2 Pole, 3 Wire, Receptacle
	Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 120-277V AC	15A 120-277V AC	15A 120-277V AC	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R
Black	—	<b>RCD101BK</b>	<b>RCD103BK</b>	<b>RCD108BKTR</b>
Gray	—	<b>RCD101GY</b>	<b>RCD103GY</b>	<b>RCD108GYTR</b>
Ivory	<b>RCD111I</b>	<b>RCD101I</b>	<b>RCD103I</b>	<b>RCD108ITR</b>
Light Almond	<b>RCD111LA</b>	<b>RCD101LA</b>	<b>RCD103LA</b>	<b>RCD108LATR</b>
White	<b>RCD111W</b>	<b>RCD101W</b>	<b>RCD103W</b>	<b>RCD108WTR</b>
 *				
Description	Single Pole Switch, 2 Pole, 3 Wire Receptacle	Two (2) Three Way Switches	Three Way Switch, Tamper-Resistant, 2 Pole, 3 Wire, Receptacle	Three Way Switch, 2 Pole, 3 Wire Receptacle
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, Side Wire
Rating	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120-277V AC	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R	15A 120V (switch) 15A 125V (recept.) NEMA 5-15R
Black	<b>RCD108BK</b>	<b>RCD303BK</b>	<b>RCD308BKTR</b>	<b>RCD308BK</b>
Gray	<b>RCD108GY</b>	<b>RCD303GY</b>	<b>RCD308GYTR</b>	<b>RCD308GY</b>
Ivory	<b>RCD108I</b>	<b>RCD303I</b>	<b>RCD308ITR</b>	<b>RCD308I</b>
Light Almond	<b>RCD108LA</b>	<b>RCD303LA</b>	<b>RCD308LATR</b>	<b>RCD308LA</b>
White	<b>RCD108W</b>	<b>RCD303W</b>	<b>RCD308WTR</b>	<b>RCD308W</b>
Description	Single Pole Switch, Pilot Light, Clear Lens, Amber Neon Bulb	Three Way Switch, Pilot Light, Clear Lens, Amber Neon Bulb	Nightlight Only	
Termination	Self-Grounding, Side Wire	Self-Grounding, Side Wire	Self-Grounding, 6" Pre-wired Stranded Wire, ½" Stripped Ends	
Rating	15A 120V	15A 120V	120V	
Black	—	—	—	
Gray	—	—	—	
Ivory	<b>RCD109I**</b>	<b>RCD309I**</b>	<b>DD100NLIV**</b>	
Light Almond	<b>RCD109LA**</b>	<b>RCD309LA**</b>	<b>DD100NLLA**</b>	
White	<b>RCD109W**</b>	<b>RCD309W**</b>	<b>DD100NLWH**</b>	

Note: \*See Technical section, page 10 for Tamper-Resistant description.  
 \*\*Requires neutral wire.

**Pilot Light Wiring Diagram**

