40 SCFM

M/I-Style Basic Flow Size 1/4”

Coupler Material	Plug Material	Max Temp.	Air Flow	Max Inlet Pressure	Seals
Brass	Case Hardened Steel Plated to Resist Rust	250° F	40 SCFM (except Push Button)	300 PSI	Buna-N



• Milton M/I-Style KWIK-CHANGE® couplers and plugs will interchange with all manufacturers who comply with the dimensional requirements of military specification MIL-C-4109.

COUPLERS

FEMALE CONNECTION

Brass Body,
Brass Sleeve

Part No.	Connection	Packaging
715 / S-715	1/4” FNPT	Box / Displayable
715BK	1/4” FNPT	Bulk
718 / S-718	3/8” FNPT	Box / Displayable
718BK	3/8” FNPT	Bulk

Prevents accidental uncoupling

Case Hardened
Steel Drag Guard

Part No.	Connection	Packaging
713	1/4” FNPT	Box
713BK	1/4” FNPT	Bulk

Push Type, Steel
Sleeve, Drag Guard

Part No.	Connection	Packaging
755 / S-755	1/4” FNPT	Box / Displayable
755BK	1/4” FNPT	Bulk

Easy to identify by button color

Push Button Safety Coupler
36 SCFM

Part No.	Connection	Packaging
S-99705	1/4” FNPT	Displayable

MALE CONNECTION

Brass Body,
Brass Sleeve

Part No.	Connection	Packaging
716 / S-716	1/4” MNPT	Box / Displayable
716BK	1/4” MNPT	Bulk
719 / S-719	3/8” MNPT	Box / Displayable
719BK	3/8” MNPT	Bulk

Push Type, Steel
Sleeve, Drag Guard

Part No.	Connection	Packaging
756	1/4” MNPT	Box

Case Hardened Steel
Drag Guard

Part No.	Connection	Packaging
714	1/4” MNPT	Box
714BK	1/4” MNPT	Bulk

1. Push once to stop airflow.
2. Push twice to release plug.

Push Button Safety Coupler
36 SCFM

Part No.	Connection	Packaging
S-99706	1/4” MNPT	Displayable

NOTE: THE “S-” PREFIX INDICATES THAT THE PRODUCT IS DISPLAYABLE.

WARNING: COUPLERS ON THIS PAGE ARE FOR AIR SHOP ONLY.