

# EK Series

## 200 AMP - 600 VOLTS



METER  
SOCKETS

CATALOGUE #	DESCRIPTION	ENCLOSURE TYPE	ENCLOSURE SIZE	WEIGHT
<b>EK400P</b>	Overhead c/w hub plate	A	15 <sup>3</sup> / <sub>8</sub> " x 8 <sup>5</sup> / <sub>8</sub> " x 5"	12 lbs.
<b>EK400L</b>	Overhead c/w 2" hub	A	15 <sup>3</sup> / <sub>8</sub> " x 8 <sup>5</sup> / <sub>8</sub> " x 5"	13 lbsca.
<b>EK400D</b>	Overhead c/w 2-2" hubs	A	15 <sup>3</sup> / <sub>8</sub> " x 8 <sup>5</sup> / <sub>8</sub> " x 5"	14 lbs.
<b>EK400DP</b>	Overhead c/w 2 hub plates, twin openings	A	15 <sup>3</sup> / <sub>8</sub> " x 8 <sup>5</sup> / <sub>8</sub> " x 5"	13 lbs.
<b>EK400M</b>	Overhead c/w master coupler	A	15 <sup>3</sup> / <sub>8</sub> " x 8 <sup>5</sup> / <sub>8</sub> " x 5"	13 lbs.
<b>EK400T</b>	Underground	B	15 <sup>3</sup> / <sub>8</sub> " x 8 <sup>5</sup> / <sub>8</sub> " x 5"	12 lbs.
<b>EK400R</b>	Comb. OH/UG approved for BC as well	D	18" x 10 x 5 <sup>3</sup> / <sub>8</sub> "	14 lbs.
<b>EK400RO</b>	Comb. OH/UG, oversize enclosure	F	18" x 12" x 5"	15 lbs.
<b>E400RO</b>	Comb. OH/UG straight lugs on line side	F	18" x 12" x 5"	15 lbs.
<b>EK400TO</b>	Underground oversize enclosure	F	18" x 12" x 5"	15 lbs.
<b>EK400ROW</b>	Comb. OH/UG c/w water heater lugs	F	18" x 12" x 5"	15 lbs.
<b>EK400ROBC</b>	Oversize enclosure for BC only	E	18" x 12" x 5 <sup>3</sup> / <sub>8</sub> "	15 lbs.

- CSA enclosure 3
- Barrel type connectors angled at 45°
- Conductor range No. 6 -250 MCM CU/AL
- Lay-in neutral (can be used with unbroken neutral wire)
- Add suffix NS for ground lug on neutral for New Brunswick only

- Field adaptable accessories
- 5th Jaw at 9 O'clock "SXK503"
- 5th Jaw at 6 O'clock "INK501"
- Insulated neutral INK200

KNOCKOUT CODE	CONDUIT SIZE
<b>AA</b>	1/2"
<b>G</b>	1 <sup>1</sup> / <sub>4</sub> ", 1 <sup>1</sup> / <sub>2</sub> ", 2", 2 <sup>1</sup> / <sub>2</sub> "
<b>F</b>	1", 1 <sup>1</sup> / <sub>4</sub> ", 1 <sup>1</sup> / <sub>2</sub> ", 2", 2 <sup>1</sup> / <sub>2</sub> ", 3"

