

Swivel Connector

Multi-Angle Non metallic Liquid Tight Connectors

- Listed under the Underwriter's Laboratories
- UL and CUL listed E197675
- Available in 1/2" and 3/4" trade size
- All nylon construction
- Resists salt water, wak acides, gasoline, alcohol, oil, grease and common solvents
- Melded of type nylon 6
- Flammability classification 94V-2: temperature index 125°C
- Swivel design can easily change from a 0-90° angle, or any in between
- Eliminate inventory as the swivel design can be substituted for a Straight or 90° connector



How it Works

- Simply loosen the centre nut, swivel fitting
- No disassembly required. Simply push the conduit or tubing onto the ferrule, tightening the domed sealing nut
- Completed assembly can then be secured in the chassis by the locknut (or first secure the connector into a NPT threaded hole)

Part Number	Description	Trade Size	K.O. Size	Std Package	Weight
C-NMSW050	Swivel Connector	16 (1/2")	16 (1/2")	25/100	3 kg.
C-NMSWB050	Swivel Connector Black	16 (1/2")	16 (1/2")	25/100	3 kg.
C-NMSW075	Swivel Connector	21 (3/4")	21 (3/4")	20/100	5.5 kg.
C-NMSWB075	Swivel Connector Black	21 (3/4")	21 (3/4")	20/100	5.5 kg.