

## SUPERSEAL® LIQUID TIGHT CONDUIT CSA FT4

SSFT4

Superseal® Type "CSA" - Hydro Tested FT4

- Hot-dipped galvanized steel core with a pressure extruded PVC jacket
- Smooth interior for easy wire pulling
- Bi-directional
- Strength and flexibility to handle stress and strain
- Used in dry, damp or wet locations.
- Resists sunlight, heat and chemical degradation
- PVC jacket 75° C
- CSA # LL63214

Work Temperature: -30° to +75°C



Superseal® CSA FT4

Part #	Trade Sizes (Inches)	Inside Diameter (Inches)	Outside Diameter (Inches)		Weight Per Coil CSA	Bend Diameter (Inches)	Standard Coils (Meters)	Standard Reels (Meters)
			Min.	Max.				
SFT4-038	12 (3/8")	12.29 (.484)	17.5 (0.690)	18.0 (.710)	10 kg	101.6 (4)	30	150/300/360
SFT4-050	16 (1/2")	15.8 (.622)	20.8 (.820)	21.3 (.840)	12 kg	152.4 (6)	30	150/300
SFT4-075	21 (3/4")	20.83 (.820)	25.2 (1.030)	26.7 (1.050)	16 kg	203.2 (8)	30	150
SFT4-100	27 (1")	26.44 (1.041)	32.8 (1.290)	33.4 (1.315)	22 kg	254 (10)	30	120
SFT4-125	35 (1 1/4")	35.05 (1.380)	41.4 (1.630)	42.2 (1.660)	16 kg	318 (12.5)	15	75
SFT4-150	41 (1 1/2")	40.01 (1.575)	47.4 (1.865)	48.3 (1.900)	20 kg	381 (15)	15	45
SFT4-200	53 (2")	51.31 (2.020)	59.4 (2.340)	60.3 (2.375)	25 kg	508 (20)	15	30
SFT4-250	63 (2 1/2")	62.99 (2.480)	72.1 (2.840)	73.0 (2.875)	18 kg	635 (25)	10	
SFT4-300	78 (3")	77.98 (3.070)	87.9 (3.460)	88.9 (3.500)	22 kg	762 (30)	10	
SFT4-400	103 (4")	101.6 (4.000)	113.3 (4.460)	114.3 (4.500)	38 kg	1016 (40)	10	

Custom lengths available upon request. Longer reel lengths are available reel deposit depending on length. Colour-Black. Other colours available upon request (blue, orange, red, yellow) Please contact our office for more details.

A company as flexible as its product..

SUPERIOR FLEXIBLE CONDUITS INC.

## Superseal® Type PCW

SSPCW

SUPERSEAL® PCW Type "CSA"

### Special Feature:

Integral copper wire RF shielding

- Used for the computer industry
- Crush resistant
- Seals out liquids and gases
- CSA # LL63214

Work Temperature 75°C



Superseal® Type "PCW"							
Part #	Trade Sizes (Inches)	Inside Diameter (Inches)	Outside Diameter (Inches)		Weight Per Coil CSA	Bend Diameter (Inches)	Standard Coils (Meters)
			Min.	Max.			
SSPCW_-038	12 (3/8")	12.29 (.484)	17.5 (.690)	18.0 (.710)	14 kg	101.6 (4)	30
SSPCW_-050	16 (1/2")	15.8 (.622)	20.8 (.820)	21.3 (.840)	16 kg	152.4 (6)	30
SSPCW_-075	21 (3/4")	20.83 (.820)	25.2 (1.030)	26.7 (1.050)	22 kg	203.2 (8)	30
SSPCW_-100	27 (1")	26.44 (1.041)	32.8 (1.290)	33.4 (1.315)	39 kg	254 (10)	30
SSPCW_-125	35 (1 1/4")	35.05 (1.380)	41.4 (1.630)	42.2 (1.660)	26 kg	318 (12.5)	15
SSPCW_-150	41 (1 1/2")	40.01 (1.575)	47.4 (1.865)	48.3 (1.900)	28 kg	381 (15)	15
SSPCW_-200	53 (2")	51.31 (2.020)	59.4 (2.340)	60.3 (2.375)	33 kg	508 (20)	15
SSPCW_-250	63 2 (1/2")	62.99 (2.480)	72.1 (2.840)	73.0 (2.875)	23 kg	635 (25)	10
SSPCW_-300	78 (3")	77.98 (3.070)	87.9 (3.460)	88.9 (3.500)	32 kg	762 (30)	10
SSPCW_-400	103 (4")	101.6 (4.000)	113.3 (4.460)	114.3 (4.500)	51 kg	1016 (40)	10

Custom lengths available upon request. Longer reel lengths are available. Reel deposit depending on length. Standard Colours - Red and Blue - Other colours available upon request. Please contact our office for more details.

## SUPERSEAL® EF (Extra Flexible)

SSEF

Superseal® Type EF - NON CSA

### Special Feature:

Conforms to both the JIC standards for dimensions and general construction.

- Inner core-corrosion resistant steel
- Indoor or outdoor use.
- Resists sunlight, heat, oil & chemical degradation
- Standard colour Gray

Work Temperature -20°C to +80°C



A company as flexible as its product...

SUPERIOR FLEXIBLE CONDUITS INC.

Superseal® Type "EF" - NON CSA							
Part #	Trade Sizes (Inches)	Inside Diameter (Inches)	Outside Diameter (Inches)		Weight Per Coil	Bend Diameter (Inches)	Standard Coils (Meters)
			Min.	Max.			
SSEFG038	12 (3/8")	12.29 (.484)	17.5 (.690)	18.0 (.710)	9 kg	76.2 (3)	30
SSEFG050	16 (1/2")	15.8 (.622)	20.8 (.820)	21.3 (.840)	11 kg	101.6 (4)	30
SSEFG075	21 (3/4")	20.83 (.820)	25.2 (1.030)	26.7 (1.050)	13 kg	127 (5)	30
SSEFG100	27 (1")	26.44 (1.041)	32.8 (1.290)	33.4 (1.315)	19 kg	177.8 (7)	30
SSEFG125	35 (1 1/4")	35.05 (1.380)	41.4 (1.630)	42.2 (1.660)	12 kg	203.2 (8)	15
SSEFG150	41 (1 1/2")	40.01 (1.575)	47.4 (1.865)	48.3 (1.900)	17 kg	228.6 (9)	15
SSEFG200	53 (2")	51.31 (2.020)	59.4 (2.340)	60.3 (2.375)	20 kg	305 (12)	15
SSEFG250	63 (2 1/2")	62.99 (2.480)	72.1 (2.840)	73.0 (2.875)	25 kg	432 (17)	8
SSEFG300	78 (3")	77.98 (3.070)	87.9 (3.460)	88.9 (3.500)	17 kg	508 (20)	8
SSEFG400	103 (4")	101.6 (4.000)	113.3 (4.460)	114.3 (4.500)	35 kg	635 (25)	8