


Industrial Grade


Maintained and Momentary Contact Extra Heavy-Duty Specification Grade Toggle Switches

Specifications and Features


- Positive switching action with center-off position
- Large silver cadmium-oxide contacts for long life, prevent sticking, welding and excessive pitting
- Clamp-type terminals accept up to #10 CU wire
- Full rated current capacity on fluorescent, tungsten and resistive loads; motor load capacity up to 80% switch current rating
- Backed by a Limited Ten-Year Warranty




1281-L



1285



1256



1257-L

BACK AND SIDE WIRED - MAINTAINED CONTACT U S

Description	Color	Cat No.		
		120/277VAC		
Rating		15A	20A	30A
Single Pole, Double Throw, Center Off	White	1281-W	1285-W	—
	Ivory	1281-I	1285-I	1287-I
	Grey	—	1285-GY	—
	Brown	1281	1285	1287
	Red	—	1285-R	—
Single Pole, Double Throw, Locking†	Black	1281-L	1285-L	1287-L
Single Pole, Double Throw, Center Off	White	1282-W	1286-W	1288-W
	Ivory	1282-I	1286-I	1288-I
	Brown	1282	1286	1288
Double Pole, Double Throw, Locking†	Ivory	—	—	1288-LI
	Black	—	—	1288-L

†Key for Locking Switch: Cat. No. 55500-PRT.

BACK AND SIDE WIRED - MOMENTARY CONTACT U S

Description	Color	Cat No.		
		120/277VAC		
Rating		15A	20A	30A
Single Pole, Double Throw, Center Off	White	1256-W	—	—
	Ivory	1256-I	1257-I	—
	Grey	1256-GY	—	—
	Brown	1256	1257	1260*
	Red	—	1257-R	—
Single Pole, Double Throw, Center Off, Locking†	Ivory	—	1257-LI	—
Single Pole, Double Throw, Center Off	Brown	—	1257-L	—
	Brown	—	—	1262*

†Key for Locking Switch: Cat. No. 55500-PRT.
CSA Certified except where indicated by*.