

Quickwire and Side Wired Quiet Framed Toggle Switches



Description	Cat. No.	Rating	Color
Single Pole, non-grounded	1451	15A-120VAC	W, I
Single Pole with ground screw	1451-2	15A-120VAC	W, I, A, T, E
Single Pole, less ears with ground screw	1451-4	15A-120VAC	W, I
3-Way, non-grounded	1453	15A-120VAC	W, I
3-Way with ground screw	1453-2	15A-120VAC	W, I, A, T, E
3-Way, less ears with ground screw	1453-4	15A-120VAC	W, I
4-Way with ground screw	54504-2	15A-120VAC	W, I, A, T, GY

Quickwire and Side Wired Illuminated Toggle Switches



Description	Cat. No.	Rating	Illumination	Toggle Color
Single Pole with ground screw	1461-LH	15A-120VAC	Amber	Clear
3-Way with ground screw	1463-LH	15A-120VAC	Amber	Clear
Single Pole with ground screw	1461-GL	15A-120VAC	Green	W, I, A, T, E
3-Way with ground screw	1463-GL	15A-120VAC	Green	W, I, A, T, E

Note: Illuminated switches do not require a neutral wire.

CO/ALR Side Wired Framed Toggle Switches



Description	Cat. No.	Rating	Color
Single Pole with ground screw	2651-2	15A-120VAC	W, I ±
3-Way with ground screw	2653-2	15A-120VAC	W, I ±

Note: CO/ALR devices are for connection to No. 12 or No. 10 AWG aluminum conductors.

COLOR

Basic Cat. Nos. denote Mahogany (Brown), not available where indicated (±). To order colors, add suffix to basic Cat. No. White (-W), Ivory (-I), Almond (-A), Light Almond (-T), Gray (-GY), Ebony (-E).

TESTING AND CODE COMPLIANCE

- UL Listed (File #E-7458)
- CSA Certified (File #LR-3413)
- NOM Certified (#057)

HORSEPOWER

15A
1/2 @120V

MATERIAL CHARACTERISTICS

Environmental: Flammability, Rated V2
Operating Temperature: -40°F to 149°F (-40°C to 65°C)



1451-W



1461-LHC



2651-W