LEVITON

Commercial Grade

Decora Plus™ Maintained and Momentary Contact Switches

Specifications and Features

- Full rated current capacity with tungsten, fluorescent or resistive loads. Motor capacity is 80% of switch rating
- Wrap-around heavy-gauge strap with locking tabs for added strength
- Back and side-wiring terminals accept both solid and stranded wire to ease installation
- Backed by a Limited Ten-Year Warranty



5657-2W

BACK AND SIDE WIRED - MOMENTARY CONTACT U S

Description	Color	Cat No.
Rating		**15A - 120/277VAC**
Single Pole,	White	5657-2W
Double Throw,	Ivory	5657-2I
Center Off	Light Almond	5657-2T
	Grey	5657-2GY
	Black	5657-2E
	Brown	5657-2



5686-2I

BACK AND SIDE WIRED - MAINTAINED CONTACT U S

Description	Color	Cat No.
Rating		**15A - 120/277VAC**
Single Pole,	White	5685-2W
Double Throw,	Ivory	5685-2I
Center Off	Light Almond	5685-2T
	Grey	5685-2GY
	Black	5685-2E
	Brown	5685-2
Double Pole,	White	5686-2W
Double Throw,	Ivory	5686-2I
Center Off	Light Almond	5686-2T

TESTING AND CODE COMPLIANCE

- UL Listed (File #E-7458)
- CSA Certified (File #LR-3413)
- NOM Certified (#057)
- Meets requirements of latest Federal Specification WS-896

HORSEPOWER

- 15A – ½ @ 120V, 2 @ 240V

MATERIAL CHARACTERISTICS

- Environmental: Flammability, UL-94 V2 Rating
- Operating Temperature: -40°C to 120°C

ELECTRICAL

- Dielectric Voltage: Withstands 1500V for 1 min.
- Overload UL 20 Test: 100 cycles of overload at 4.8 times rated current
- Temp. Rise: 30° C max at full rated current
- Endurance: UL 20/Fed Spec 50,000 cycles min., tungsten filament lamp load (Fed.Spec.) WS896E, SP, DP, 3-Way, 4-Way, Pilot Light, Illum., Key Lock

MECHANICAL

- Terminal I.D.: Brass-Hot, Black-Hot, White-Neutral, Green-Grounding
- Terminal Accomm.: #14-#10 AWG back wired; #14-#12 AWG side wired
- Product I.D.: Ratings are permanently stamped on device strap
- Torque Range: 12-14 inch pounds