

Residential Grade

Decora® LED Sensor Guide Lights

Our new LED Sensor Guide Light Series unites Leviton's quality decora wiring devices with energy-saving LED Guide Lights for a smart combination. The Sensor LEDs turn ON and OFF automatically in Switch/Guide Light or Tamper-resistant Receptacle/Guide Light combinations, as well as a full LED Guide Light version that's perfect for hallways or stairways.

Specifications and Features

All Devices

- Impact-resistant face and body
- Long-lasting energy-efficient LED with long life expectancy no bulbs to replace
- Light sensor provides automatic ON/OFF features
- All devices have a self grounding clip
- Fits standard wall boxes
- Back or side wired

Tamper Resistant Receptacle/Guide Light

- Uses two LEDs
- Shutter mechanism inside the recptacle blocks access to the contacts unless a two-prong plug is inserted, helping ensure foregin objects will be locked out
- Complies with section 406.11 of the 2008 NEC Code

Combination Switch/Guide Light

- Uses two LEDs
- Single Pole
- Neutral Required

Full LED Guide Light

- Uses three LEDs
- Color Change Kits available for select models

COLORS

Decora devices are offered in a wide range of colors and finishes. To order colors, add suffix to Cat No.

White Ivory Almond Light Almond
(-W) (-I) (-A) (-T)



Residential Grade

T6525

DECORA® COMBINATION DEVICES* (D) 60.

Description	Color	Cat No.	
NEMA			
		5-15R	
Rating		15A-125VAC	
Decora Tamper Resistant	White	T6525-W	
Receptacle/LED Guide Light	Ivory	T6525-I	
	Almond	T6525-A	
	Light Almond	T6525-T	
Rating		15A-125VAC	
Decora Single Pole Switch/	White	6526-W	
LED Guide Light	lvory	6526-l	
	Almond	6526-A	
	Light Almond	6526-T	
Rating		1W-120VAC	
Decora Full LED Guide Light	White	6527-W	
	Ivory	6527-I	
	Almond	6527-A	
	Light Almond	6527-T	



TESTING AND CODE COMPLIANCE

- UL Listed (File #E-7458)
- CSA Certified (File #LR-3413)
- NOM Certified (#057)


HORSEPOWER

• 15A - 1/2 @ 120V


MATERIAL CHARACTERISTICS

Environmental: Flammability UL-94, V2 Rating Operating Temperature: -40°C to 120°C


DIMENSIONS



1.33 (33.8) (71.1) 1.08 (27.4)



4.18 (106.2) 3.28 (83.3) 1.60 (40.6)



Decora 6527 Full LED Guidelight

Decora 6526 Switch LED Guidelight