

## Decora® Blank and Bulkhead Connector Fillers

Decora® Blank and Bulkhead Connector Fillers						
Description	Brown	Ivory	White	Grey	Almond	Black
(A) Single Hole, .406 Diameter, used for bulkhead connectors, plastic Individual polybag pack*	80400	80400-I	80400-W	80400-GY	80400-A	80400-E
(B) Blank Plastic.* Individual polybag pack*	80414	80414-I	80414-W	80414-GY	80414-A	80414-E
Blank for Use with Decora Plus Snap-on Individual polybag pack** -	-	80314-I	80314-W	80314-GY	80314-A	-

\* For use with standard Decora wallplates only, sold separately.

\*\* Note: Includes three single gang subplates for 2-, 3- and 4-gang Decora Plus wallplate configurations where a blank is required.




## Decora® Wallplates

Smooth-faced, dust-resistant wallplates for standard Decora-style flush mount wall jacks (above). Choose from standard or snap-on styles in single-gang or double-gang configurations. Indoor plates come with color-matched mounting screws. UL Listed; meets NEMA standard WD-1.


Standard Decora® Wallplates						
Description	Brown	Ivory	White	Grey	Almond	Black
(C) Single-Gang Individual polybag pack	80401	80401-I	80401-W	80401-GY	80401-A	80401-E
Double-Gang Individual polybag pack	80409	80409-I	80409-W	80409-GY	80409-A	80409-E

Note: For single- and double-gang Decora wallplates in stainless steel order 84401-40 or 84409-40.



## Decora Plus® Snap-On Wallplates with Hidden Mounting Screws

Decora Plus® Snap-On Wallplates with Hidden Mounting Screws						
Description	Brown	Ivory	White	Grey	Almond	Black
(D) Single-Gang Individual polybag pack	80301	80301-I	80301-W	80301-GY	80301-A	80301-E
Double-Gang Individual polybag pack	80309	80309-I	80309-W	80309-GY	80309-A	80309-E



## Decora® Outdoor Wallplate Covers

Weather-resistant self-closing cover protects devices located outdoors, such as phone or audio jacks that are located near decks, pools, hot tubs or patios. Use with Decora wallplates.

Decora® Outdoor Wallplate Covers		
Description	Grey	White
(E) Decora Outdoor Cover - Horizontal, Die-Cast Zinc Boxed unit pack	4990	-
Decora Outdoor Cover - Vertical, Die-Cast Zinc Boxed unit pack	4992	-
Decora Outdoor Cover - Horizontal, Plastic Boxed unit pack	4996-GY	4996-W
Decora Outdoor Cover - Vertical, Plastic Boxed unit pack	4998-GY	4998-W







**Wallplate Replacement Screws (5/16" - 6x32 threads)**

DESCRIPTION	CAT. NO.	DESCRIPTION	CAT. NO.
Almond 100 per box	82400	Ivory 100 per box	86400
Black 100 per box	83400	Gray 100 per box	87400
Stainless Steel 100 per box	84400	White 100 per box	88400
Brown 100 per box	85400	Red 100 per box	89400



Decora Replacement Screws




**Standard Size Plastic Adapters**

DESCRIPTION	CAT. NO.	COLOR*
		<small>Basic Cat. No. Denotes Mahogany</small>
Dimmer Shaft (.406" hole) 	80400	I, W, GY, E, A
Blank (no hole) 	80414	I, W, GY, E, A
CATV Jack 	80381-I	W, GY, E, A
Wallbox Adapter Extends shallow wallbox to fit GFCI/Decora devices 	6197	I, W



80400-A/80414-I

**Decora® Plus Standard Size Plastic Adapters**

DESCRIPTION	CAT. NO.	COLOR*
CATV Jack 	80381	I, W, GY, E, A
Blank (no hole) 	80314	I, W, GY, E, A
4-Gang Template 	80300	Brown only

All devices are UL Listed and CSA Certified.

**TESTING & CODE COMPLIANCE**

- Backed by a Limited Two-Year Warranty

**\*COLOR**

Colors available as listed. For other color selections, add suffix to catalog numbers as follows: Ivory (-I), White (-W), Gray (-GY), Black (-E), Almond (-A).

**MATERIAL CHARACTERISTICS**

Environmental: Flammability UL-94, V2 Rating  
 Operating Temperature: -40°C to 120°C

For more information regarding matching wallplates, colors, materials, single and multi-gang, refer to Wallplates, section G.







Decora Replacement Screws




*Wallplate Replacement Screws (5/16"-6x32 threads)*

DESCRIPTION	CAT. NO.	DESCRIPTION	CAT. NO.
<b>Almond</b> 100 per box	82400	<b>Ivory</b> 100 per box	86400
<b>Black</b> 100 per box	83400	<b>Gray</b> 100 per box	87400
<b>Stainless Steel</b> 100 per box	84400	<b>White</b> 100 per box	88400
<b>Brown</b> 100 per box	85400	<b>Red</b> 100 per box	89400

*Standard Size Plastic Adapters*

DESCRIPTION	CAT. NO.	COLOR*
		<small>Basic Cat. No. Denotes Mahogany</small>
	80400	I, W, GY, E, A
<b>Dimmer Shaft (.406" hole)</b>		
	80414	I, W, GY, E, A
<b>Blank (no hole)</b>		
	80381-I	W, GY, E, A
<b>CATV Jack</b>		
	6197	I, W
<b>Wallbox Adapter</b> Extends shallow wallbox to fit GFCI/Decora devices		

*Decora® Plus Standard Size Plastic Adapters*

DESCRIPTION	CAT. NO.	COLOR*
	80381	I, W, GY, E, A
<b>CATV Jack</b>		
	80314	I, W, GY, E, A
<b>Blank (no hole)</b>		
	80300	Brown only
<b>4-Gang Template</b>		

All devices are UL Listed and CSA Certified.



80400-A/80414-I

**TESTING & CODE COMPLIANCE**

- Backed by a Limited Two-Year Warranty

**\*COLOR**

Colors available as listed. For other color selections, add suffix to catalog numbers as follows: Ivory (-I), White (-W), Gray (-GY), Black (-E), Almond (-A).

**MATERIAL CHARACTERISTICS**

Environmental: Flammability UL-94, V2 Rating  
Operating Temperature: -40°C to 120°C

For more information regarding matching wallplates, colors, materials, single and multi-gang, refer to Wallplates, section G.







*Wallplate Replacement Screws (5/16"-6x32 threads)*

DESCRIPTION	CAT. NO.	DESCRIPTION	CAT. NO.
<b>Almond</b> 100 per box	82400	<b>Ivory</b> 100 per box	86400
<b>Black</b> 100 per box	83400	<b>Gray</b> 100 per box	87400
<b>Stainless Steel</b> 100 per box	84400	<b>White</b> 100 per box	88400
<b>Brown</b> 100 per box	85400	<b>Red</b> 100 per box	89400



*Standard Size Plastic Adapters*

DESCRIPTION	CAT. NO.	COLOR*
		<small>Basic Cat. No. Denotes Mahogany</small>
	80400	I, W, GY, E, A
<b>Dimmer Shaft (.406" hole)</b>		
	80414	I, W, GY, E, A
<b>Blank (no hole)</b>		
	80381-I	W, GY, E, A
<b>CATV Jack</b>		
	6197	I, W
<b>Wallbox Adapter</b> Extends shallow wallbox to fit GFCI/Decora devices		

**TESTING & CODE COMPLIANCE**

- Backed by a Limited Two-Year Warranty




**\*COLOR**

Colors available as listed. For other color selections, add suffix to catalog numbers as follows: Ivory (-I), White (-W), Gray (-GY), Black (-E), Almond (-A).

**MATERIAL CHARACTERISTICS**

Environmental: Flammability UL-94, V2 Rating  
Operating Temperature: -40°C to 120°C

*Decora® Plus Standard Size Plastic Adapters*

DESCRIPTION	CAT. NO.	COLOR*
	80381	I, W, GY, E, A
<b>CATV Jack</b>		
	80314	I, W, GY, E, A
<b>Blank (no hole)</b>		
	80300	Brown only
<b>4-Gang Template</b>		

All devices are UL Listed and CSA Certified.

For more information regarding matching wallplates, colors, materials, single and multi-gang, refer to Wallplates, section G.