

#### **Residential and Commercial Grade**

# Wallplates and Weather-Resistant Covers

Leviton Decora Plus™ and Decora® Designer Wallplates — available in a wide spectrum of colors and styles — can add subtle elegance to any home. You can go modern with Decora Plus screwless, snap-on wallplates, which install fast and flawlessly. Sleek, versatile and convenient, they now come in a midway size that gives even greater coverage, and can hide unsightly wall surface irregularities. All Leviton Decorative Wallplates can stand up to heavy use while coordinating perfectly with paint or wallcoverings. Think of them as the finishing touch to giving a home its signature look.



Decora devices are offered in a wide range of colors and finishes. To order colors, add suffix to Cat No.



(-1)











(-E)













Steel





Aluminum

**Features and Benefits** 

#### All Decora Wallplates

- Accent any wall covering with a wide selection of colors and finishes
- Smooth face and rounded edges resist dust accumulation
- Color-matched metal mounting screws supplied

#### Thermoset Wallplates

- Designed for high dielectric strength and arc resistance
- Meets or exceeds UL 514 testing requirements
- Resistant to fading, discoloration, grease, oils, organic solvents and moisture scratches
- Limited Two-Year Warranty



#### **Residential and Commercial Grade**

### Thermoplastic Wallplates

- Molded thermoplastic for maximum resistance to impact, abrasion, fading and discoloration
- Resistant to mechanical stress associated with high abuse applications
- Limited Ten-Year Warranty

# Metal Wallplates (Commercial Grade)

- Rounded edges to prevent injury and wall damage
- Deluxe stainless steel is non-magnetic Type 302, .032" thick
- Standard stainless steel Type 430, .032" thick, also available
- Brass is 70/30 alloy 260, .040" thick
- Aluminum is 3004 alloy, .040" thick
- Limited Ten-Year Warranty

### Decora Plus™

### **Specifications and Features**

- Sleek, smooth contemporary styling with no mounting screws and no subplate screws for ease of installation and cleaning
- Decora compatible two-piece kit allows easy use with any Decora installation
- Constructed of durable polycarbonate to with stand abuse
- Screwless subplate offers ease of installation exclusive "Hook n' Snap" feature provides an easy, convenient and truly screwless wallplate installation

# DECORA PLUS SCREWLESS SNAP-ON (WITH SCREWLESS SUBPLATE) (1) (1)

Description	Color	Cat. No. Standard Size
 1-Gang	White	80301-SW
<u> </u>	Ivory	80301-SI
	Almond	80301-SA
	Lt. Almond	80301-ST
	Grey	80301-SGY
	Black	80301-SE
	Brown	80301-S
2-Gang	White	80309-SW
_	Ivory	80309-SI
	Almond	80309-SA
	Lt. Almond	80309-ST
	Grey	80309-SGY
	Black	80309-SE
	Brown	80309-S
 3-Gang	White	80311-SW
	Ivory	80311-SI
	Almond	80311-SA
	Lt. Almond	80311-ST
	Black	80311-SE
	Brown	80311-S



# **Residential and Commercial Grade**

Description	Color	Cat. No. Standard Size	
4-Gang	White	80312-SW	
	lvory	80312-SI	
	Almond	80312-SA	
	Lt. Almond	80312-ST	
	Black	80312-SE	
	Brown	80312-S	
5-Gang	White	80321-SW	
	lvory	80321-SI	
	Almond	80321-SA	
	Lt. Almond	80321-ST	
6-Gang	White	80326-SW	
	Ivory	80326-SI	
	Almond	80326-SA	
	Lt. Almond	80326-ST	

#### **TESTING AND CODE COMPLIANCE**

- UL Listed (File #E-13397)
- Meets NEMA Standards WD-1, WD-6
- CSA Certified (File #LR-16347)
- NOM Certified (#057)


#### **MATERIAL CHARACTERISTICS**

Environmental: Flammability UL-94, V2 Rating Operating Temperature: -40°C to 120°C

### **DIMENSIONS**

#### Standard Size

80301-S



NOTE: Add 1.81" (46.0mm) for each additional gang



# **Residential and Commercial Grade**

# Decora® Standard

### **Specifications and Features**

- Accent any wall covering with a wide selection of colors and finishes
- Smooth face and rounded edges resist dust accumulation
- Color-matched mounting screws supplied
- Mounting screws on one-gang Thermoplastic (Nylon) are preinstalled and captive

# **DECORA STANDARD SIZE (4) (5)**

1	Description	Color	Thermoset	Thermoplastic (Nylon)		Metal	
Industry Standard		P26	N26	Indu	stry Standard		
			Cat. No.	Cat. No.			Cat. No.
	1-Gang	White	80401-W	80401-NW	Aluminum	A26	83401
		lvory	80401-I	80401-NI	Brass	B26	81401
		Almond	80401-A	80401-NA	Polished Brass		81401-PB
		Lt. Almond	80401-T	80401-NT	Non-Magnetic S/S	SN26-N	84401-40
		Grey	80401-GY	80401-NGY			
		Black	80401-E	80401-NE			
		Brown	80401	80401-N			
		Red	_	80401-NR			
		Blue	_	80401-NB			
Industry Standard			P262	N262			
	2-Gang	White	80409-W	80409-NW	Aluminum	A262	83409
	_	lvory	80409-1	80409-NI	Brass	B262	81409
		Almond	80409-A	80409-NA	Polished Brass		81409-PB
		Lt. Almond	80409-T	80409-NT	Non-Magnetic S/S	S262-N	84409-40
		Grey	80409-GY	80409-NGY			
		Black	80409-E	80409-NE			
		Brown	80409	80409-N			
		Red	_	80409-NR			
Industry Standard			P263	N263			
	3-Gang	White	80411-W	80411-NW	Aluminum	A263	83411
		lvory	80411-I	80411-NI	Brass	B263	81411
		Almond	80411-A	80411-NA	Polished Brass		81411-PB
		Lt. Almond	80411-T	80411-NT	Non-Magnetic S/S	S263-N	84411-40
		Grey	80411-GY	80411-NGY			
		Black	80411-E	_			
		Brown	80411	80411-N			
Industry Standard			P264	N264			
	4-Gang	White	80412-W	80412-NW	Brass	B264	81412
		lvory	80412-I	80412-NI	Non-Magnetic S/S	S264-N	84412-40
		Almond	80412-A	80412-NA			
		Lt. Almond	80412-T	80412-NT			
		Grey	80412-GY	_			
		Black	80412-E	_			
		Brown	80412	80412-N			



**Residential and Commercial Grade** 


# **DECORA® STANDARD SIZE (4) 66.**

Description	Color	Thermoset	Thermoplastic		Metal	
			(Nylon)			
		P265		Industry Standard		d
		Cat. No.	Cat. No.			Cat. No.
5-Gang	White	80423-W		Brass	B265	81423
	Ivory	80423-I		Non-Magnetic S/S	S265-N	84423-40
	Almond	80423-A				
	Lt. Almond	80423-T				
	Grey	80423-GY				
	Black	80423-E				
	Brown	80423				
		P262				
6-Gang	White	80436-W		Non-Magnetic S/S	S266-N	84436-40
	lvory	80436-I				
	Almond	80436-A				
	Lt. Almond	80436-T				
	Grey	80436-GY				
	Black	80436-E				
	Brown	80436				
		P267				
7-Gang	White	80407-W±				
	Ivory	80407-l±				
		P264	N264			
8-Gang	White	80408-W±				
	5-Gang 6-Gang 7-Gang	5-Gang White Ivory Almond Lt. Almond Grey Black Brown  6-Gang White Ivory Almond Lt. Almond Grey Black Brown  7-Gang White Ivory	P265  Cat. No.  5-Gang White 80423-W lvory 80423-I Almond 80423-A Lt. Almond 80423-T Grey 80423-E Brown 80423  Brown 80423  P262  6-Gang White 80436-W lvory 80436-I Almond 80436-A Lt. Almond 80436-GY Black 80436-E Brown 80436  F267  7-Gang White 80407-W± lvory 80407-I±  P264	P265   Cat. No.   Cat. No.	P265   Industrial	P265

<sup>±</sup> Painted Metal Wallplates

# **DIMENSIONS**

### Standard Size Single-Gang



NOTE: Add 1.81" (46.0mm) for each additional gang



# **Residential and Commercial Grade**

# Decora® Midway

# **Specifications and Features**

- Midway plates can be used to hide wall surface irregularities
- Full 0.375" taller and wider than standard wallplates
- Available in a wide selection of sizes and colors to complement any wall color or covering
- Smooth face and rounded edges resist dust accumulation
- Color-matched mounting screws supplied

# **DECORA® MIDWAY SIZE (4) (5)**

	Description	Color	Thermoset	Thermoplastic (Nylon)	Metal	
Industry Standard			P26	N26	Industry Standard	
			Cat. No.	Cat. No		Cat. No.
<u></u>	1-Gang	White	80601-W	PJ26-W	Non-Magnetic S/S	SSJ26
		lvory	80601-I	PJ26-I		
<u>-</u>		Almond	80601-A	PJ26-A		
		Lt. Almond	80601-T	PJ26-T		
		Grey	_	PJ26-GY		
		Black	_	PJ26-E		
		Brown	80601	PJ26		
		Red	_	PJ26-R		
		Blue	_	PJ26-BU		
Industry Standard			SPJ262	PJ262		
2-Gang	2-Gang	White	80609-W	PJ262-W	Non-Magnetic S/S	SJ262
		lvory	80609-I	PJ262-I		
<u></u>		Almond	80609-A	PJ262-A		
		Lt. Almond	80609-T	PJ262-T		
		Grey	_	PJ262-GY		
		Black	_	PJ262-E		
		Brown	80609	PJ262		
Industry Standard			SPJ263	PJ263		
· · ·	3-Gang	White	80611-W	PJ263-W	Non-Magnetic S/S	SJ263
		lvory	80611-I	PJ263-I		
		Almond	80611-A	PJ263-A		
		Lt. Almond	80611-T	PJ263-T		
		Grey	_	PJ263-GY		
		Brown	80611	_		
Industry Standard			SPJ264	PJ264		
	4-Gang	White	80612-W	PJ264-W		
		lvory	80612-I	PJ264-I		
• • • •		Almond	80612-A	PJ264-A		
		Lt. Almond	80612-T	PJ264-T		
		Grey	_	PJ264-GY		
		Brown	80612	_		



# **Residential and Commercial Grade**

# Decora® Oversize

### **Specifications and Features**


- Available in a wide selection of sizes and colors to complement any wall color or covering
- Smooth face and rounded edges resist dust accumulation
- Color-matched mounting screws supplied

# **DECORA OVERSIZE (1) (5)**

	Description	Color Therm	Thermoset	Meta	Metal		
Industry Standard			P026	Industry St	Industry Standard		
			Cat. No.		Cat. No.		
	1-Gang	White	88601-W	Non-Magnetic S/S <b>SO26</b>	<b>S</b> SO26		
<b>.</b>		lvory	86601-I				
		Almond	82601-A				
Industry Standard			P0262				
	2-Gang	White	88602-W	Non-Magnetic S/S <b>S026</b>	<b>2</b> SO262		
		lvory	86602-I				
		Almond	82602-A				
	3-Gang			Non-Magnetic S/S <b>S026</b>	<b>3</b> S0263		


#### **DIMENSIONS**

### Midway Size Single-Gang



Midway wallplates can be mounted onto larger-volume outlet boxes and/or used to hide wall irregularities. Midway wallplates are a full 0.375" higher and wider than standard size wallplates.

#### **Oversized Single-Gang**



Oversized wallplates are used to conceal greater wall irregularities than those hidden by Midway wallplates. Oversized wallplates are a full 0.75" higher and wider than standard size wallplates.

NOTE: Add 1.81" (46.0mm) for each additional gang.

#### **Residential and Commercial Grade**

# **Traditional Wallplates**

Familiar and functional, Leviton Traditional Wallplates are designed for use with Traditional Leviton devices. They represent styles and form factors that have stood the test of time. Their clean lines work in virtually any location, whether in new or retrofit construction, and they install quickly and easily. Leviton offers Traditional Wallplates in a vast array of colors and configurations.



#### **Features and Benefits**

#### All Leviton Wallplates

- Easy to clean, smooth finish
- Non-combustible
- Color-matched metal mounting screws supplied
- UL Listed and CSA Certified
- Conforms to NEMA and ANSI Standards

#### Thermoset (Plastic) Wallplates (Residential Grade)

- Designed for high dielectric strength and arc resistance
- Meets or exceeds UL514 testing requirements
- Resistant to fading, discoloration, grease, oil, organic solvents and moisture scratches
- Limited Two-Year Warranty

#### Thermoplastic (Nylon) Wallplates (Commercial Grade)

- Molded thermoplastic for maximum resistance to impact, abrasion, fading and discoloration
- Resistant to mechanical stress associated with high abuse applications
- Limited Ten-Year Warranty

### Metal Wallplates (Commercial Grade)

- Rounded edges to prevent injury and wall damage
- Deluxe stainless steel is non-magnetic Type 302, .032" thick.
- Standard stainless steel Type 430, .032" thick, also available
- Brass is 70/30 alloy 260, .040" thick
- Limited Ten-Year Warranty