



5601-2T
in 80301-ST

DECORA® Designer Rocker Switches

Features & Benefits

- Switch frame shields against dust and fits in wallplate to prevent rocker binding
- Side Wire and Quickwire (No. 12 or No. 14 copper or copper clad wire) push-in terminal wiring options
- Sturdy construction for long service life
- Full-rated current capacity with tungsten, fluorescent or resistive loads. Motor capacity is 80% of switch rating
- Conform to all NEMA standard specifications
- Complements every decor

15 AMP Quickwire Push-In and Side Wired 120/277V AC

Description	Cat. No.	Color*
Single-Pole	5601	Mahogany
	5601-I	Ivory
	5601-W	White
	5601-2	Mahogany
	5601-2I	Ivory
	5601-2W	White
	5601-2A	Almond
	5601-2T	Light Almond
	5601-2E	Ebony
	5601-2GY	Gray
	5601-S2I†	Ivory
	5601-S2W†	White
	5601-S2A†	Almond
Double-Pole	5602-2I	Ivory
	5602-2W	White
	5602-2A	Almond
	5602-2T	Light Almond
	5602-2E	Ebony
Three-Way	5603	Mahogany
	5603-I	Ivory
	5603-W	White
	5603-2	Mahogany
	5603-2I	Ivory
	5603-2W	White
	5603-2A	Almond
	5603-2T	Light Almond
	5603-2E	Ebony
	5603-2GY	Gray
	5603-S2I†	Ivory
	5603-S2W†	White
5603-S2A†	Almond	
Four-Way	5604-2	Mahogany
	5604-2I	Ivory
	5604-2W	White
	5604-2A	Almond
	5604-2T	Light Almond
	5604-2E	Ebony
	5604-2GY	Gray

Testing & Code Compliance

- UL Listed (File #E-7458)
- CSA Certified (File #LR-3413)
- NOM Certified (#057)
- Backed by a Limited Two-Year Warranty

Material Characteristics

Environmental: Flammability UL-94, V2 Rating
Operating Temperature: -40°C to 120°C

*Color

Rocker/frame color available as listed.

Horsepower

15 AMP

1/2 @ 120V

2 @ 240V

Dimensional drawings on page T2.

For more information regarding coordinating wallplates, colors, materials, single and multi-gang, refer to Wallplates, section D.

Note: To order Decora rocker switches with grounding screw add suffix -2 (i.e. 5601-2I)

†Self-grounding when installed in a properly grounded metal wallbox.