

Accessories and Spare Parts

Accessories for 3RT, 3RH contactors and contactor relays



3RT19 24-5A.01 3RT19 34-5A.01 3RT19 44-5A.01 3RT19 45-5A.01 3RT19 45-5A.02 3RT19 55-5A. 3RT19 55.5N..

For contactors		Rated control supply voltage U_c		Screw terminals	Weight per PU approx.	Rated control supply voltage U_c		Screw terminals	Weight per PU approx.	
Size	Type			Order No.	kg	Type			Order No.	kg
Magnetic Coils - AC operation						Magnetic Coils - DC operation				
S0	3RT10 2..	24V	50/60 Hz	3RT19 24-5AC21	0.100					
	3RT13 2..	110V	50/60 Hz	3RT19 24-5AG21	0.100					
	3RT15 2..	230V	50/60 Hz	3RT19 24-5AL21	0.100					
		400V	50 Hz	3RT19 24-5AV21	0.100					
S2	3RT10 34	24V	50/60 Hz	3RT19 34-5AC21	0.120	3RT10 3	24V DC	3RT19 34-5BB41	0.650	
		110V	50/60 Hz	3RT19 34-5AG21	0.120	3RT13 3	110V DC	3RT19 34-5BF41	0.650	
		230V	50/60 Hz	3RT19 34-5AL21	0.120	3RT15 3	220V DC	3RT19 34-5BM41	0.650	
		400V	50 Hz	3RT19 34-5AV21	0.120					
	3RT10 35	24V	50/60 Hz	3RT19 35-5AC21	0.120					
	3RT10 36	110V	50/60 Hz	3RT19 35-5AG21	0.120					
	3RT13 3.	230V	50/60 Hz	3RT19 35-5AL21	0.120					
	3RT15 3.	400V	50 Hz	3RT19 35-5AV21	0.120					
	S3	3RT10 44	24V	50/60 Hz	3RT19 44-5AC21	0.190	3RT10 4	24V DC	3RT19 44-5BB41	1.000
			110V	50/60 Hz	3RT19 44-5AG21	0.190	3RT13 4	110V DC	3RT19 44-5BF41	1.000
			230V	50/60 Hz	3RT19 44-5AL21	0.190	3RT15 4	220V DC	3RT19 44-5BM41	1.000
			400V	50 Hz	3RT19 44-5AV21	0.190	3RT15 4			
3RT10 45		24V	50/60 Hz	3RT19 45-5AC21	0.190					
3RT10 46		110V	50/60 Hz	3RT19 45-5AG21	0.190					
3RT13 4.		230V	50/60 Hz	3RT19 45-5AL21	0.190					
3RT14 46		400V	50 Hz	3RT19 45-5AV21	0.190					
3RT15 4.										
Withdrawable coils										
<i>Conventional operating mechanism</i>					<i>Solid-state operating mechanism</i>			For 24V DC PLC output		
S6	3RT10 5	110...127V AC/DC		3RT19 55-5AB31	0.650	3RT10 5	96...127V AC/DC		3RT19 55-5NF31	0.650
	3RT14 5	220...240V AC/DC		3RT19 55-5AF31		3RT14 5	200...277V AC/DC		3RT19 55-5NP41	
S10	3RT10 6	110...127V AC/DC		3RT19 65-5AB31	0.850	3RT10 6	96...127V AC/DC		3RT19 55-5NF31	0.900
		220...240V AC/DC		3RT19 65-5AF31			200...277V AC/DC		3RT19 55-5NP31	
	3RT14 6	110...127V AC/DC		3RT19 66-5AB31	1.000	3RT14 6	96...127V AC/DC		3RT19 66-5NF31	0.650
		220...240V AC/DC		3RT19 66-5AF31			200...277V AC/DC		3RT19 66-5NP31	
	vacuum contactors			3RT19 66-5AP31	1.000	vacuum contactors			3RT19 66-5NP31	0.650
S12	3RT10 7	110...127V AC/DC		3RT19 75-5AB31	1.300	3RT10 7	96...127V AC/DC		3RT19 75-5NF31	0.650
		220...240V AC/DC		3RT19 75-5AF31			200...277V AC/DC		3RT19 75-5NP31	
	3RT14 7	110...127V AC/DC		3RT19 75-5AB31	1.300	3RT14 7	96...127V AC/DC		3RT19 75-5NF31	0.650
		220...240V AC/DC		3RT19 75-5AF31			200...277V AC/DC		3RT19 75-5NP31	
	vacuum contactors			3RT19 75-5AP31	1.300	vacuum contactors			3RT19 75-5NP31	0.650
For 24 V DC PLC output/PLC relay output, with remaining lifetime indicator (RLT)										
(Withdrawable coil with lateral solid-state module)										
S6	3RT10 5	96...127V AC/DC		3RT19 55-5PF31	0.650					
	3RT14 5	200...277V AC/DC		3RT19 55-5PP31		0.650				
S6	3RT10 6	96...127V AC/DC		3RT19 65-5PF31	1.300					
	3RT14 6	200...277V AC/DC		3RT19 65-5PP31		1.300				
S612	3RT10 7	96...127V AC/DC		3RT19 75-5PF31	1.300					
	3RT14 7	200...277V AC/DC		3RT19 75-5PP31		1.300				