

SURGE SUPPRESSOR, DIODE COMBINATION WITH LED, DC 24 V, FOR MOTOR CONTACTORS SZ S0,



General technical data:		
product brand name		SIRIUS
Product designation		surge suppressor
Size of contactor		S0
Design of the surge suppressor		with diode assemblies
Ambient temperature		
• during storage	°C	-40 ... +80
• during operation	°C	-25 ... +60
Control circuit/ Control:		
Type of voltage of the control supply voltage		DC
Control supply voltage 1		
• at DC		
— Rated value	V	24
Installation/ mounting/ dimensions:		
mounting position		any
Mounting type		clip-on
Width	mm	30
Height	mm	19

Depth

mm

12

Certificates/ approvals:

Certificate of suitability

CE / UL / CSA / CCC

General Product Approval

Declaration of
Conformity

Test
Certificates

Shipping Approval



EG-Konf.

[spezielle
Prüfbescheinigung](#)
[n](#)



ABS



Shipping Approval



DNV



GL



LRS



PRS



RINA



RMRS

other

[Bestätigungen](#)

[Umweltbestätigung](#)



VDE

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT29261MR00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT29261MR00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT29261MR00&lang=en



last modified:

20.07.2015