







SIRIUS CABLE-OPER. SWITCH METAL HOUSING, 2X M25X1.5  
2NO+2NC, LATCHES AC.EN ISO13850 BUTTON RESET 2-SIDE  
OPERATION FOR CABLES UP TO 2X75M



<b>Product designation</b>	cable-operated switch
<b>General technical data:</b>	
<b>Protection class IP</b>	IP65
<b>Equipment marking</b>	
<ul style="list-style-type: none"> <li>• acc. to DIN EN 61346-2</li> <li>• acc. to DIN EN 81346-2</li> </ul>	<p>S</p> <p>S</p>
<b>Enclosure:</b>	
<b>Material of the enclosure</b>	metal
<b>Product component</b>	
<ul style="list-style-type: none"> <li>• EMERGENCY STOP device</li> </ul>	Yes
<b>Color</b>	
<ul style="list-style-type: none"> <li>• of top part of the enclosure</li> </ul>	grey
<b>Ambient conditions:</b>	
<b>Ambient temperature</b>	
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	-25 ... +70 °C
<b>Installation/ mounting/ dimensions:</b>	
<b>Mounting type</b>	screw fixing

Height	160 mm
Width	128 mm
Depth	54 mm

#### Certificates/ approvals:

General Product Approval	Declaration of Conformity	Shipping Approval
 CCC	 EG-Konf.	 ABS
 CSA		 LRS

#### Shipping Approval



#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

##### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SE71601AE00>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SE71601AE00>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SE71601AE00&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SE71601AE00&lang=en)

last modified:

22.07.2015