

OUTPUT INTERFACE, OPTOCOUPLER IN TWO-TIER DESIGN
1NO, TRANSISTOR, 24V DC 1.5A, SCREW CONNECTION



Figure similar

General technical data:

Type of voltage	DC
Control supply voltage	
• at DC Rated value	
— minimum	11 V
— maximum	30 V
Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	1
Number of CO contacts for auxiliary contacts	0
Switching behavior	monostable
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Equipment marking acc. to DIN EN 61346-2	K

Mechanical data:




Type of electrical connection	screw-type terminals
Type of electrical connection Plug-in socket	No
Design of the relay operating mechanism	poled
Design of the switching function positively driven	No
Product component Plug-in socket	No

Width	6.2 mm
Height	60 mm
Depth	62 mm

Ambient conditions:

Protection class IP	IP20
Ambient temperature during operation	-25 ... +60 °C

Certificates/ approvals:

General Product Approval	Declaration of Conformity	Test Certificates	other
 CCC	 UL	 EAC	 EG-Konf.
		spezielle Prüfbescheinigung n	sonstig

other

[Bestätigungen](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX70043PB54>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX70043PB54>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX70043PB54&lang=en

last modified:

17.07.2015