

SITOP DC UPS MODULE 15A WITHOUT INTERF.
 SITOP DC UPS MODULE 24 V/15 A UNINTERRUPTIBLE POWER
 SUPPLY WITHOUT INTERFACE INPUT: 24 V DC/16 A OUTPUT:
 24 V DC/15 A



Input	
Supply voltage at DC Rated value	24 V
Voltage curve at input	DC
input voltage range	22 ... 29 V DC
Mains buffering	
Type of energy storage	with batteries
Charging current	
• 1	0.35 A
• 2	0.7 A
Output	
Output voltage	
• in normal operation at DC Rated value	24 V
• in buffering mode at DC Rated value	24 V
Formula for output voltage	$V_{in} - \text{approx. } 0.5 \text{ V}$
ON-delay time typical	1 s
Voltage increase time of the output voltage typical	60 ms
Output current Rated value	15 A
Property of the output Short-circuit proof	Yes

Active power supplied typical	360 W
Efficiency	
Efficiency in percent	
<ul style="list-style-type: none"> at rated output current at rated output current typical 	96.2 %
<ul style="list-style-type: none"> in case of accumulator operation typical 	96 %
Active power loss	
<ul style="list-style-type: none"> at rated output current at rated output current typical 	14 W
<ul style="list-style-type: none"> in case of accumulator operation typical 	15 W
Protection and monitoring	
Product function	
<ul style="list-style-type: none"> reverse polarity protection against energy storage unit polarity reversal 	Yes
<ul style="list-style-type: none"> reverse polarity protection against input voltage polarity reversal 	Yes
Signaling	
Display version	
<ul style="list-style-type: none"> for normal operation 	Normal operation: LED green (OK), floating changeover contact "Bat/OK" to setting "OK" ("OK" means: Voltage of the supplying power supply unit is greater than cut-in threshold set at the DC UPS module); Lack of buffer standby: LED red (alarm), floating changeover contact "Alarm/Bat" to setting "Alarm"; Battery replacement required: LED red (alarm) flashing with approx. 0.25 Hz, floating changeover contact "Alarm/Bat" switching with approx. 0.25 Hz; Energy storage > 85%: LED green (Bat > 85%), floating NO contact "Bat > 85" closed; Permissible contact current capacity: DC 60 V/1 A or AC 30 V /1 A
<ul style="list-style-type: none"> in buffering mode 	Buffered mode: LED yellow (Bat), floating changeover contact "OK/Bat" to setting "Bat"; Prewarning battery voltage < 20.4 VDC: LED red (alarm), floating changeover contact "Alarm/Bat" to setting "Alarm"; Energy storage > 85%: LED green (Bat > 85%), floating NO contact "Bat > 85" closed
Interface	
Product component PC interface	No
Design of the interface	without
Safety	
Galvanic isolation between entrance and outlet	No
Operating resource protection class	Class III
Certificate of suitability	
<ul style="list-style-type: none"> CE marking 	Yes
<ul style="list-style-type: none"> UL approval 	Yes
<ul style="list-style-type: none"> as approval for USA 	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259

<ul style="list-style-type: none"> • relating to ATEX • C-Tick 	-
Shipbuilding approval	No
Protection class IP	-
	IP20

EMC

Standard	
<ul style="list-style-type: none"> • for emitted interference • for interference immunity 	EN 55022 Class B EN 61000-6-2

Operating data

Ambient temperature	
<ul style="list-style-type: none"> • during operation • during transport • during storage 	-25 ... +60 °C -40 ... +85 °C -40 ... +85 °C
Environmental category acc. to IEC 60721	Climate class 3K3, no condensation

Mechanics

Type of electrical connection	screw-type terminals
<ul style="list-style-type: none"> • at input • at output • for battery module • for control circuit and status message 	24 V DC: 2 screw terminals for 1 ... 4 mm ² /17 ... 11 AWG 24 V DC: 4 screw terminals for 1 ... 4 mm ² /17 ... 11 AWG 24 V DC: 2 screw terminals for 1 ... 4 mm ² /17 ... 11 AWG 10 screw terminals for 0.5 ... 2.5 mm ² /20 ... 13 AWG
Width of the enclosure	50 mm
Height of the enclosure	125 mm
Depth of the enclosure	125 mm
Required spacing	
<ul style="list-style-type: none"> • top • bottom • left • right 	50 mm 50 mm 0 mm 0 mm
Net weight	0.4 kg
Product property of the enclosure housing for side-by-side mounting	Yes
Mounting type	Snaps onto DIN rail EN 60715 35x7.5/15
Electrical accessories	Battery module
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)