PROFIBUS

Communication for SIMATIC S7-1200

CM 1242-5

Overview



DP-M	DP-S	FMS	PG/OP	S7
	•			6_KN_X_1022

The CM 1242-5 communication module is used to connect a SIMATIC S7-1200 to PROFIBUS as a DP slave and has the following characteristics:

- PROFIBUS DPV1 slave in accordance with IEC 61158
- Module replacement without PG supported
- Power is supplied via the backplane bus so that no extra cabling is required
- Support of all standard baud rates from 9.6 kbit/s to 12 Mbit/s
- Compact industry-standard enclosure in S7-1200 design for mounting on a standard mounting rail
- Fast commissioning thanks to easy configuration using STEP 7 without additional programming overhead

The CM 1242-5 is intended for use in factory automation. Low-cost PROFIBUS-based automation solutions can be created on the basis of the S7-1200 for optimal production.

Ordering data	Order No.
CM 1242-5 communication module Communication module for electrical connection of SIMATIC S7-1200 to PROFIBUS as a DPV1 slave	6GK7 242-5DX30-0XE0
Accessories	
PROFIBUS FastConnect connector RS485	
With 90° cable outlet; insulation displacement technology, max. transmission rate 12 Mbit/s • Without PG interface • With PG interface	6ES7 972-0BA52-0XA0 6ES7 972-0BB52-0XA0
PROFIBUS FC standard cable	6XV1 830-0EH10
2-core bus cable, shielded, special design for fast mounting, delivery unit: max. 1000 m, minimum order 20 m, sold by the meter	
PROFIBUS FastConnect stripping tool	6GK1 905-6AA00
Stripping tool for fast stripping of the PROFIBUS FastConnect bus cable	
PROFIBUS bus terminal 12M	6GK1 500-0AA10
Bus terminal for connection of PROFIBUS nodes at up to 12 Mbit/s with connecting cable	
STEP 7 Basic engineering software V11	
Target system: SIMATIC S7-1200 controllers and the associated I/O Requirement: Windows XP Home SP3, Windows XP Professional SP3 (32 bit), Windows 7 Home Premium (32 bit), Windows 7 Professional (32 bit), Windows 7 Enterprise (32 bit), Windows 7 Ultimate (32 bit), Microsoft Server 2003 R2 Std. SP2 (32 bit), Microsoft Server 2008 Std. SP2 (32 bit) Delivery package: German, English, Chinese, Italian, French, Spanish	
Single licenseUpgrade STEP 7 Basic V10.5	6ES7 822-0AA01-0YA0 6ES7 822-0AA01-0YE0
to STEP 7 Basic V11, single license Powerpack STEP 7 Basic V11 to STEP 7 Prof. V11,	6ES7 822-1AA01-0YC5

6ES7 822-0AA01-0YA7

floating license

• STEP 7 Basic V11, trial license