

## Data sheet

6ES7972-0BB42-0XA0

**Product type designation**  
Product description

**PROFIBUS bus connector, RS485, screw, with PG socket, 35°**  
PROFIBUS bus connector, RS485, screw, mwith PG socket, 35°  
SIMATIC DP, BUS CONNECTOR FOR PROFIBUS UP TO 12  
MBIT/S WITH TILTED CABLE OUTLET, 15,8 X 54 X 39,5 MM  
(WXHXD), TERMINAT. RESIST. WITH ISOLAT. FUNCTION, WITH  
PG SOCKET



Suitability for use	For connecting PROFIBUS nodes to the PROFIBUS bus cable
<b>Transmission rate</b>	
Transfer rate / with PROFIBUS DP	9.6 kbit/s ... 12 Mbit/s
<b>Interfaces</b>	
Number of electrical connections	
• for PROFIBUS cables	2
• for network components or terminal equipment	1
Type of electrical connection	
• for PROFIBUS cables	Screw
Type of electrical connection / FastConnect	No
<b>Mechanical data</b>	
Design of terminating resistor	Integrated resistor combination that can be selected with slide switch
Material / of the enclosure	plastic
<b>Design, dimensions and weight</b>	
Width	15.8 mm

Height	54 mm
Depth	39.5 mm
Net weight	67 g

### Permitted ambient conditions

Ambient temperature	
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Protection class IP	IP20

### Product properties, functions, components / general

Product property	
• silicon-free	Yes
Product component	
• PG connection socket	Yes
• strain relief	Yes

### Standards, specifications, approvals

Certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes

**last modified:** 17.07.2015