

Ordering data	Article No.	Ordering data	Article No.
CPU 414-2 Main memory 1 MB, power supply 24 V DC, MPI/PROFIBUS DP master interface, slot for memory card, incl. slot number labels	6ES7414-2XK05-0AB0	Slot number plates 1 set (spare part)	6ES7912-0AA00-0AA0
CPU 414-3 Main memory 2.8 MB, power supply 24 V DC, MPI/PROFIBUS DP master interface, PROFIBUS DP master interface, slot for memory card, module slots for 1 IF module, incl. slot number labels	6ES7414-3XM05-0AB0	SIMATIC Manual Collection Electronic manuals on DVD, multilingual: LOGO!, SIMADYN, SIMATIC bus components, SIMATIC C7, SIMATIC distributed I/O, SIMATIC HMI, SIMATIC Sensors, SIMATIC NET, SIMATIC PC Based Automation, SIMATIC PCS 7, SIMATIC PG/PC, SIMATIC S7, SIMATIC Software, SIMATIC TDC	6ES7998-8XC01-8YE0
CPU 414-3 PN/DP Main memory 4 MB, power supply 24 V DC, MPI/PROFIBUS DP master interface, PROFINET interface, slot for memory card, module slot for 1 IF module, incl. slot number labels	6ES7414-3EM06-0AB0	SIMATIC Manual Collection update service for 1 year Current "Manual Collection" DVD and the three subsequent updates	6ES7998-8XC01-8YE2
Memory card RAM		PROFIBUS bus components	
64 KB	6ES7952-0AF00-0AA0	RS 485 bus connector with 90° cable outlet Max. transfer rate 12 Mbit/s	
256 KB	6ES7952-1AH00-0AA0	• Without PG interface	6ES7972-0BA12-0XA0
1 MB	6ES7952-1AK00-0AA0	• With PG interface	6ES7972-0BB12-0XA0
2 MB	6ES7952-1AL00-0AA0	RS 485 bus connector with angled cable outlet Max. transfer rate 12 Mbit/s	
4 MB	6ES7952-1AM00-0AA0	• Without PG interface	6ES7972-0BA42-0XA0
8 MB	6ES7952-1AP00-0AA0	• With PG interface	6ES7972-0BB42-0XA0
16 MB	6ES7952-1AS00-0AA0	RS 485 bus connector with 90° cable outlet for FastConnect connection system Max. transfer rate 12 Mbit/s	
64 MB	6ES7952-1AY00-0AA0	• without PG interface	
FEPRAM memory card		- 1 unit	6ES7972-0BA52-0XA0
64 KB	6ES7952-0KF00-0AA0	- 100 units	6ES7972-0BA52-0XB0
256 KB	6ES7952-0KH00-0AA0	• with PG interface	
1 MB	6ES7952-1KK00-0AA0	- 1 unit	6ES7972-0BB52-0XA0
2 MB	6ES7952-1KL00-0AA0	- 100 units	6ES7972-0BB52-0XB0
4 MB	6ES7952-1KM00-0AA0	RS 485 bus connector with axial cable outlet For SIMATIC OP, for connection to PPI, MPI, PROFIBUS	6GK1500-0EA02
8 MB	6ES7952-1KP00-0AA0	PROFIBUS FastConnect bus cable Standard type with special design for fast mounting, 2-core, shielded, sold by the meter; max. delivery unit 1 000 m, minimum ordering quantity 20 m	6XV1830-0EH10
16 MB	6ES7952-1KS00-0AA0	RS 485 repeater for PROFIBUS Transmission rate up to 12 Mbit/s; 24 V DC; IP20 enclosure	6ES7972-0AA02-0XA0
32 MB	6ES7952-1KT00-0AA0		
64 MB	6ES7952-1KY00-0AA0		
MPI cable for connection of SIMATIC S7 and PG via MPI; 5 m in length	6ES7901-0BF00-0AA0		
IF 964-DP interface module To connect an additional DP line; for CPU 414-3, CPU 414-3 PN/DP, CPU 416-3, CPU 416-3 PN/DP, CPU 417-4	6ES7964-2AA04-0AB0		