

### Product type designation

### Antenna ANT 30

RF300/ RF200/ MOBY E ANT 30 ANTENNA PVC, CABLE LENGTH 3M IP 65, -25 TO +70 DEGR/C, M30X58 MM, MAX. DISTANCE: 24 MM (DEPENDING ON MDS)



### Wireless frequencies

Transmission frequency / Rated value	13.56 MHz
--------------------------------------	-----------

### Electrical data

Type of electrical connection / of the antenna	M8, 4-pin
Design of plug-in connection	male

### Mechanical data

Material	Crastin
Color	Pastel turquoise
Tightening torque / of the screw for securing the equipment / maximum	3 N·m
Mounting distance <ul style="list-style-type: none"> <li>relating to metal surfaces / recommended / minimum</li> </ul>	0 m

### Permitted ambient conditions

Ambient temperature <ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> </ul>	<p>-25 ... +70 °C</p> <p>-40 ... +85 °C</p>
--	---

• during transport	-40 ... +85 °C
Protection class IP	IP67, front
Shock resistance	according to EN 60721-3-7 Class 7M2
Shock acceleration	500 m/s <sup>2</sup>
Vibrational acceleration	200 m/s <sup>2</sup>

### Design, dimensions and weight

Depth	58 mm
Diameter	30 mm
Net weight	150 g
Mounting type	2 plastic cscrew nuts M30 x 1.5
Cable length / of antenna cable	3 m

### Standards, specifications, approvals

Certificate of suitability	CE, FCC, IC, cULus, Ex approval only together with 6GT2801-4AB10
----------------------------	--

### Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> <li>• to website: Selector SIMATIC NET SELECTION TOOL</li> <li>• to website: Industrial communication</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Image database</li> <li>• to website: CAx Download Manager</li> <li>• to website: Industry Online Support</li> </ul>	<ul style="list-style-type: none"> <li><a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a></li> <li><a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a></li> <li><a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a></li> <li><a href="http://www.siemens.com/automation/net/catalog">http://www.siemens.com/automation/net/catalog</a></li> <li><a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a></li> <li><a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a></li> <li><a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a></li> </ul>

**last modified:** 17.07.2015