

Ordering data (continued)	Order No.	Order No.
Accessories		
IE FC TP Standard Cable GP 2 x 2 (Type A) 4-core, shielded TP installation cable for connection to IE FC Outlet RJ45 / IE FC RJ45 Plug; PROFINET-compliant; with UL approval; sold by the meter; max. length 1000 m, minimum order 20 m	6XV1 840-2AH10	Length: • 0.3 m • 0.5 m • 1.0 m • 1.5 m • 2.0 m • 3.0 m • 5.0 m • 10 m • 15 m 6XV1 870-8AE30 6XV1 870-8AE50 6XV1 870-8AH10 6XV1 870-8AH15 6XV1 870-8AH20 6XV1 870-8AH30 6XV1 870-8AH50 6XV1 870-8AN10 6XV1 870-8AN15
FO Standard Cable GP 50/125/1400 ^{1) 2)} Multimode cable, sold by the meter; max. length 1000 m; minimum order 20 m;	6XV1 873-2A	IE M12 Panel Feedthrough Control cabinet feedthrough for transition from 4-pole, D-coded M12 interface (IP65/IP67) to RJ45 socket (IP20) • 1 pack = 5 units 6GK1 901-0DM20-2AA5
FO Robust Cable GP 4E9/125/90 Singlemode cable, sold by the meter; max. length 1000 m; minimum order 20 m	6XV1 843-2R	IE Power M12 Cable Connector PRO Socket for connecting SCALANCE W-700/SCALANCE X208PRO for 24 V DC supply; 4-pole, A-coded, with installation instructions 6GK1 907-0DC10-6AA3
FC FO Standard Cable GP 62.5/200/230 FC FO standard cable for fixed routing indoors with PVC sheath; sold by the meter; max. length 1000 m; minimum order 20 m	6XV1 847-2A	Signaling Contact M12 Cable Connector PRO Socket for connecting SCALANCE X208PRO for signaling contact; 5-pole, B-coded, with installation instructions 6GK1 908-0DC10-6AA3
IE FC RJ45 Plug 180 2 x 2 RJ45 plug connector for Industrial Ethernet with a rugged metal enclosure and integrated insulation displacement contacts for connecting Industrial Ethernet FC installation cables; with 180° cable outlet; for network components and CPs/CPU with Industrial Ethernet interface • 1 pack = 1 unit • 1 pack = 10 units • 1 pack = 50 units	6GK1 901-1BB10-2AA0 6GK1 901-1BB10-2AB0 6GK1 901-1BB10-2AE0	SITOP compact 24 V/ 0.6 A 1-phase power supply with wide-range input 85 – 264 V AC/110 – 300 V DC, stabilized output voltage 24 V, rated output current value 0.6 A, slim design 6EP1 331-5BA00
FC BFOC Plug Screw connector for on-site assembly on FC fiber-optic cable; (1 pack = 20 units + cleaning cloths)	6GK1 900-1GB00-0AC0	PS791-1PRO Power Supply AC/DC power supply, 10 W, IP65 (-20 to +60 °C) for SCALANCE X208PRO, input: AC 85 V – 265 V, output: 24 V DC, metal housing, Scope of supply: AC power 3+PE cable connector, DC power cord M12, installation materials, manuals German/English 6GK5 791-1PS00-0AA6
IE FC M12 Plug PRO M12 plug connector for connection of Industrial Ethernet FC installation cables; 4-pole, D-coded, metal enclosure, IP65 degree of protection, pin insert; 180° cable outlet; for network components and Industrial Ethernet stations with IP65/IP67 degree of protection • 1 pack = 1 unit • 1 pack = 8 units	6GK1 901-0DB20-6AA0 6GK1 901-0DB20-6AA8	C-PLUG Swap medium for simple replacement of devices in the event of a fault; for storing configuration or engineering and application data; can be used for SIMATIC NET products with C-PLUG slot 6GK1 900-0AB00
IE Connecting Cable M12-180/M12-180 Pre-assembled IE FC TP trailing cable GP 2 x 2 (PROFINET type C) with two 4-pole M12 plugs, 4-pole, D-coded, IP65/IP67 degree of protection;		More information To assist in selecting the right Industrial Ethernet switches as well as configuration of modular versions, the SIMATIC NET Selection Tool is available: Online version: www.siemens.com/snst Offline version: www.siemens.com/snst-download