

SIGNALLING COLUMN STEADY LIGHT BLUE,  
12...240V AC/DC



General technical data:		
product brand name		SIRIUS
Product component Light source		No
Design of the optical signal		continous light
Type of voltage of the operating voltage		AC/DC
Operating voltage		
• at DC Rated value	V	230 ... 12
• at AC at 50 Hz Rated value	V	12 ... 230
• at AC at 60 Hz Rated value	V	12 ... 230
Equipment marking acc. to DIN EN 61346-2		P

Mechanical data:		
Outer diameter of the signal column element	mm	70

Lamp:		
Type of light source		filament lamp / LED

Ambient conditions:		
Ambient temperature during operation	°C	-20 ... +60
Protection class IP		IP65
Height	mm	65.5

Width

mm

70

Certificates/ approvals:

General Product Approval

EMC

Declaration of  
Conformity

Shipping Approval



UL



C-TICK



EG-Konf.



DNV

Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrymall>

**Cax online generator**



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=8WD44001AF>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/8WD44001AF>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=8WD44001AF&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=8WD44001AF&lang=en)



WB:8444: 8WD44...\_ALL

last modified:

17.07.2015