

SIGNALLING COLUMNS, ACCESSORIES LED AC/DC
24V, BA 15D, YELLOW



Figure similar

General technical data:

| | | |
|--|---|--------|
| product brand name | | SIRIUS |
| Type of voltage of the operating voltage | | AC/DC |
| Operating voltage | | |
| • 1 at DC Rated value | V | 24 |
| • 1 at AC at 50 Hz Rated value | V | 24 |
| • 1 at AC at 60 Hz Rated value | V | 24 |
| Equipment marking acc. to DIN EN 61346-2 | | P |

Mechanical data:

| | | |
|---|----|----|
| Outer diameter of the signal column element | mm | 70 |
|---|----|----|

Lamp:

| | | |
|----------------------|--|-----|
| Type of light source | | LED |
|----------------------|--|-----|

Ambient conditions:

| | | |
|--------------------------------------|----|-------------|
| Ambient temperature during operation | °C | -20 ... +60 |
| Height | mm | 45 |
| Width | mm | 20 |

Certificates/ approvals:

| | | | |
|--------------------------|-----|---------------------------|-------------------|
| General Product Approval | EMC | Declaration of Conformity | Shipping Approval |
|--------------------------|-----|---------------------------|-------------------|



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=8WD44286XD>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WD44286XD>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=8WD44286XD&lang=en

last modified:

17.07.2015